

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T. 32 S. T. S. R. 8 W. R.W.W.M.

MOKE-CHAPMAN CO., EUGENE, ORE. 21881

C.S. File No. 54/36

JOHN M. POWELL  
Frank Jones & W. Penley  
March & April, 1968  
C. S. File No. 54/65

60  
Cl. Corner to Sec. 1, T33-8W. and Sec. 6, T33-7W.  
Found - Stone 20x14x10 with 6 notches at section corner.  
24" D.Fir, now 26" Snag, S.58°W. 37.0 ft., bark scribing "T33 R BT".  
No trace of other BT.  
Set - Brass Cap at Cor. Mkd: County Surveyor's R T 33 S R  
Office 8 S 1 | S 6 7  
1968 W W  
New BT's: 14" D.Fir S.14°E. 65.7 ft. mkd. T33S R7W S6 CC CS BT.  
6" Pine S.41°W. 45.7 ft. mkd. S 1 CC CS BT.  
Note - This corner lies 150 ft. East of logging road.

61  
Section Corner to Secs. 1 & 12, T32-8W. and Secs. 6 & 7, T32-7W.  
Found - Unrecorded 3/4" Iron Pipe at Section Corner.  
Orig. 22" D.Fir, now down, S.8°W. 43.5 ft., bark scribing visible.  
Orig. Pine Stump N.80°E. 4.0 ft., no evidence. T 32 S  
Set - Brass Cap at Cor. Mkd: County Surveyor's R S 1 | S 6 R  
Office, 1968 8W S 12 | S 7 7W  
New BT's: 8" Laurel S.41°E. 4.4 ft. mkd. T32S R7W S7 CS BT.  
12" D.Fir S.42°W. 19.5 ft. mkd. T32S R8W S12 CS BT.  
10" D.Fir N.56°W. 14.0 ft. mkd. T32S R8W S1 CS BT.  
12" D.Fir N.64°E. 38.0 ft. mkd. T32S R7W S6 CS BT.

62  
1/4 Corner to Sections 1 and 2.  
Found - 14x10x6 Stone at 1/4 Cor., chisel marks visible, stone firmly  
in ground.  
50" S.Pine, now 55" Snag, N.35°W. 75.2 ft.  
18" S.Pine, now 36", N.16°E. 69.3 ft., shows scar.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T32S R8W  
Office, 1968 1/4 S 2 | S 1  
New BT's: 6" Live Oak N.10°W. 20.0 ft. mkd. 1/4 S 2 CS BT.  
7" Live Oak S.27°E. 22.3 ft. mkd. 1/4 S 1 CS BT.  
Note - This corner lies on fairly steep west slope.

63  
Section Corner to Sections 22 - 23 - 26 - 27.  
Found - 10", now 13" Maple, N.12°W. 29.0 ft., tree has been opened,  
face burnt, but fragmentary scribing visible.  
10" D.Fir, now gone, but bear. & dist. to old stump hole good.  
2 Alder BT's. not found.  
Call on creek 19.0 ft. E.; at this time find to be about 9.0 ft.  
Set - Brass Cap at Cor.Mkd: County Surveyor's T32S R8W  
Office S 22 | S 23  
1968 S 27 | S 26  
New BT's: 10" Maple S.19°E. 15.4 ft. mkd. T32S R8W S26 CS BT.  
31" D.Fir S.44°W. 21.9 ft. mkd. T32S R8W S27 CS BT.  
12" L.Oak N.34°E. 61.4 ft. mkd. T32S R8W S23 CS BT.  
13" L.Oak West 28.5 ft. mkd. T32S R8W S22 CS BT.

64  
Section Corner to Sections 25 - 26 - 35 - 36.  
Found - No trace of 1 1/4" Iron Pipe, See Ren. #3.  
Orig. 10", now 10" Laurel, N.40°E. 34.3 ft., found scribing, "BT".  
Orig. 36", now 38" D.Fir, S.80°E. 13.9 ft., faint bark scribe "T 2 R".  
Orig. 40", now 38" B.Fir, S.68°W. 11.2 ft., no marks visible.  
Orig. 14", now 17" Laurel, N.50°W. 39.6 ft.  
Set - Brass Cap at Cor.Mkd: County Surveyor's T32S R8W  
Office S 26 | S 25  
1968 S 35 | S 36  
New BT's: 8" Live Oak N.20°E. 21.3 ft. mkd. S25 CS BT.  
Reblzd.&Rescbd: 38" D.Fir S.68°W. 11.2 ft. mkd. T32S R8W S35 CS BT.  
38" D.Fir S.80°E. 13.9 ft. mkd. T32S R8W S36 CS BT.  
17" Laurel N.50°W. 39.6 ft. mkd. T32S R8W S26 CS BT.