

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T. S. R. 8 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

65

Section Corner to Sections 4 - 5 - 8 - 9.

Found - 1" Drill Steel at Sec. Cor., See Ren. #15.

42" D. Fir, now stob, S. 65° E. 14.5 ft., bark scribed T32S R8W S9 CS BT.

36" D. Fir, now 36", N. 58° E. 27.8 ft., scribing visible.

24", now 25" D. Fir, N. 54° W. 16.2 ft., scribe visible "T32SR8W S5CSET".

New BT: 40" D. Fir S. 10° E. 73.7 ft. mkd. T32S R8W S9 CS BT.

No other trees available.

Note - This corner lies 50.0 ft. west of West Fork Creek Road.

66

Section Corner to Sections 9 - 10 - 15 - 16.

Found - Orig. 6" Laurel Stob, N. 53° W. 33.0 ft., no scribing.

Orig. 24", now 40" D. Fir, S. 28° W. 34.3 ft., faint bark scribe "R8WBT".

No trace of other BT/s. nor Stone. *REN #5*

Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1968

T 32 S	R 8 W
S 9	S 10
S 16	S 15

New BT's: 8" Laurel N. 53° W. 28.8 ft. mkd. T32S R8W S9 CS BT. # 128

8" Pine N. 83° E. 31.7 ft. mkd. T32S R8W S10 CS BT.

5" Pine East 33.0 ft. mkd. S15 CS BT.

Reblzd. & Rescribed: 40" D. Fir S. 28° W. 34.3 ft. mkd. T32S R8W S16 CS BT.

67

Section Corner to Sections 1 - 2 - 11 - 12

Found - Unrecorded 1" Iron Pipe, not at record bearing & distance, (See Note)

30" D. Fir, now 50", S. 20° W. 43.6 ft., faint bark scribe.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1968

T 32 S	R 8 W
S 2	S 1
S 11	S 12

New BT's: 7" Tan Oak N. 85° W. 14.2 ft., mkd. T32S R8W S2 CS BT.

16" D. Fir N. 22° E. 26.8 ft. mkd. T32S R8W S1 CS BT.

15" Tan Oak S. 77° E. 18.7 ft. mkd. T32S R8W S12 CS BT.

Reblzd. & Bark Scribed: 50" D. Fir S. 20° W. 43.6 ft. mkd. T32S R8W S11 CS BT.

Note - Iron Pipe N. 20° E. 1.0 ft.

68

Section Corner to Sections 16 - 17 - 20 - 21.

Found - Orig. 16", now 28" D. Fir, S. 67° E. 7.9 ft., faint scribe visible.

Orig. 30", now 42" D. Fir, N. 54° W. 14.5 ft., bark scribe visible.

Orig. 6" Laurel, now down, S. 2° W. 12.5 ft., scribe found "S", & other marks. No trace of N.E. BT. (Hole).

Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1968

T 32 S	R 8 W
S 17	S 16
S 20	S 21

Reblzd. & Rescbd: 28" D. Fir S. 67° E. 7.9 ft. mkd. T32S R8W S21 CS BT.

42" D. Fir N. 54° W. 14.5 ft. mkd. T32S R8W S17 CS BT.

New BT's: 8" Maple S. 30° W. 19.4 ft. mkd. T32S R8W S20 CS BT.

39" D. Fir N. 4° E. 33.6 ft. mkd. T32S R8W S16 CS BT.

69

Section Corner to Sections 26 - 27 - 34 - 35. *See 2007 BLK resurvey*

Found - 36", now 43" D. Fir, N. 50° W. 22.4 ft., shows faint but not legible scribe marks.

8", now 12" Laurel, center rotten, N. 15° E. 13.2 ft.

15", now 32" D. Fir, S. 36½° W. (Rec. S. 44° W.) 25.1 ft., faint scribe visible.

6", now 21" D. Fir, S. 44° E. 19.7 ft. (Rec. 21.1) no marks visible.

Set = Brass Cap at Cor. Mkd: County Surveyor's Office 1968

T 32 S	R 8 W
S 27	S 26
S 34	S 35

Reblzd. & Resbrbd: 43" D. Fir N. 50° W. 22.4 ft. mkd. T32S R8W S27 CS BT.

32" D. Fir S. 36½° W. 25.1 ft. mkd. T32S R8W S34 CS BT.

12" Laurel N. 15° E. 13.2 ft. mkd. T32S R8W S26 CS BT.

21" D. Fir S. 44° E. 19.7 ft. mkd. T32S R8W S35 CS BT.

John M. Powell
Frank Jones & W. Penley
April, 1968
C. S. File No. 54/65

*FP. OK DC50
9/22/92 CS #0462*