

**Douglas County Surveyor's Record of
Government Corners Renewed**

T. 32 S. T. S. R. 8 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

(continued)

Set - Brass Cap at $\frac{1}{4}$ Cor. Mkd: County Surveyor's Office 1968 T 32 S R 8 W
S 27
S 34

New BT's: 6" Tan Oak S. 26° W. 5.1 ft. mkd. $\frac{1}{4}$ S34 CS BT.
 23" D. Fir N. 20° E. 19.7 ft. mkd. $\frac{1}{4}$ S27 CS BT.

76

Section Corner to Sections 27 - 28 - 33 - 34.

Found - 16x14x12 Stone at corner, 3 notches on E. - 1 on the S.
 Orig. 14", now 20" D. Fir, N. 54° E. 25.1 ft. (slope) bark scribe faint.
 Orig. 4", now 8" Chinquapin, S. 45° E. 4.0 ft., shows scar.
 Orig. 15", now 31" D. Fir, S. 61° W. 40.3 ft., scribe visible "W".
 Orig. 12" D. Fir, now stump, N. 58° W. 26.4 ft.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1968 T 32 S R 8 W
S 28 | S 27
S 33 | S 34

Reblzd. & Rescbd: 31" D. Fir S. 61° W. 40.3 ft. mkd. T32S R8W S33 CS BT.
 20" D. Fir N. 54° E. 22.6 ft. mkd. T32S R8W S27 CS BT.

New BT: 19" Cedar N. 78° W. 12.7 ft. mkd. T32S R8W S28 CS BT.

77

$\frac{1}{4}$ Corner to Sections 15 and 22.

Found - Orig. 60" Pine Corner Tree, now Snag, old "X" & cruiser's marks.
 Orig. 24" D. Fir, now down & rotten, N. 30° W. 32.3 ft., found part
 of "S" scribe on bark under tree.
 No trace of S. E. BT.

Set - Brass Cap on N. side of Pine Snag Mkd: County Surveyor's Office, 1968 T 32 S R 8 W
S 15
S 22

New BT's: 8" Tan Oak N. 30° W. 40.1 ft. mkd. $\frac{1}{4}$ S15 CS BT.
 22" D. Fir S. 30° W. 39.0 ft. mkd. $\frac{1}{4}$ S22 CS BT.

78

$\frac{1}{4}$ Corner to Sections 31 and 32.

Found - 36" D. Fir, now 25' Stob, N. 80° W. 15.2 ft., old axe work.
 22", now 36" D. Fir, S. 50° E. 47.5 ft., old axe work
 No scribing, however, both trees are approximate size
 and good bear. & dist. Also call at creek of 1 ch. south hits very
 good. Old scribed post at corner point not of record. This corner
 also used since 1944, forest location tag.

Set - Brass Cap at $\frac{1}{4}$ Cor. Mkd: County Surveyor's Office, 1968 T 32 S R 8 W
S 31 | S 32

New BT: 12" D. Fir N. 63° W. 11.8 ft. mkd. " $\frac{1}{4}$ S31 CS BT".
 Reblzd. & Resrbd: 36" D. Fir S. 50° E. 47.5 ft. mkd. $\frac{1}{4}$ S32 CS BT.

79

$\frac{1}{4}$ Corner to Sections 8 and 17.

Found - 30", now 46" D. Fir, South 15.1 ft., scribe visible " $\frac{1}{4}$ S".
 No trace of N. E. BT., small Alder.

Set - Brass Cap at $\frac{1}{4}$ Cor. Mkd: County Surveyor's Office 1968 T 32 S R 8 W
S 8
S 17

New BT: 11" Maple N. 50° E. 30.5 ft. mkd. $\frac{1}{4}$ S 8 CS BT.
 Reblzd. & Resrbd: 46" D. Fir South 15.1 ft. mkd. $\frac{1}{4}$ S17 CS BT.

5/2/68

80

$\frac{1}{4}$ Corner to Section 32 only, T32-8W.

Found - 10x8x4 Stone at $\frac{1}{4}$ corner mkd. " $\frac{1}{4}$ " on North face.
 8" D. Fir, now snag, N. 9° E. 3.3 ft., scribe visible "S".
 6" D. Fir, now 7", N. 49° E. 11.9 ft., shows good scar.

Set - Brass Cap at $\frac{1}{4}$ Cor. Mkd: County Surveyor's Office 1968 Douglas Co. T32S S 32 R8
T33S Josp. Co. W

New BT: 8" D. Fir N. 18° E. 6.8 ft. mkd. $\frac{1}{4}$ S32 SC CS BT.
 Note - This corner lies on steep north slope approx. 125.0 ft.
 East of draw, NE - SW.

5/6/68

132

John M. Powell
 Frank Jones & W. Penley
 April & May, 1968
 C. S. File No. 54/65