

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T. 32 S. T. S. R. 8 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

81

$\frac{1}{4}$  Corner Section 33 only, T32-8W.  
 Found - Corner Stone 15x10x6, mkd. " $\frac{1}{4}$ ".  
 20", now 36" D.Fir, N.36°E. 227.0 ft., shows good scar.  
 24", now 26" D.Fir, N.52°W. 93.1 ft., open & show scribing " $\frac{1}{4}$ ".  
 Set - Brass Cap at  $\frac{1}{4}$  Cor. Mkd: County Surveyor's T 32 S R  
 Office Doug. Co. S 33 8  
 1968 Josp. Co. T 33 S W  
 New BT: 5" Tan Oak N.68 $\frac{1}{2}$ °E. 8.7 ft. mkd. S 33 CS BT.  
 Note - There were no other BT's. in range for scribing. Top of spur  
 bears west 162.0 ft.

82

Section Corner to Sections 32 & 33, T32-8W.  
 Found - No trace of corner stone. - Sec. Corner falls in shoulder of Road.  
 30", now 38" Pine, N.8°E. 33.0 ft. scribe visible, "3" "8" & others.  
 N.W. Bearing Tree falls in Road.  
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R  
 Office Doug. Co. S 32 | S 33 8  
 1968 Josp. Co. S 4 W  
 New BT: No trees available to the North. T 33 S  
 12" D. Fir S.10°W. 64.1 ft. mkd. T33S R8W S4 SC CS BT.  
 Note - This corner lies on E. edge of Road in mound of stone.

RE-RENEWED, SEE CORNER NO. #115

83

Section Corner to Sections 31 and 32, T32-8W.  
 Found - No trace of Corner Stone.  
 32" D.Fir, now snag, N.47°E. 15.8 ft. scribe visible "32S R8S31 SC".  
 26", now 29" D.Fir, N. 26° W. 19.8 ft., shows good scar.  
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R  
 Office Doug. Co. S 31 | S 32 8  
 1968 Josp. Co. S 5 W  
 New BT: 7" D. Fir N.62°W. 56.2 ft. mkd. T32S R8W S31 SC CS BT.  
 No other trees in area.  
 Note - This corner lies approx. 200.0 ft. S. of ridge top, running E-W.

84

Section Corner to Sections 34 and 35 only, T32-8W.  
 Found - 12x10x4 Stone "SC" mkd. on N. face.  
 15", now 17" D.Fir, N.24°E. 18.5 ft., shows good scar.  
 18", now D.Fir Stump, N.45°W. 41.6 ft. scribe visible "BT".  
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R  
 Office Doug. Co. S 34 | S 35 8  
 1968 Josp. Co. S 2 W  
 New BT: 14" D. Fir N. 77° W. 33.1 ft. mkd. T32S R8W S34 SC CS BT.  
 Note - This corner lies approximately 50.0 ft. N. of small ravine.

85

Section Corner to Sections 33 and 34 only, T32-8W.  
 Found - 16x14x9 Stone with 3 grooves on E. & W. sides. #116  
 24", now 32" D.Fir, N.71°E. (Rec. N. 68°E) 95.0 ft., all bark scribe gone.  
 16", now 24" D.Fir, N.48°W. 13.9 ft., bark scribe visible "8 W #".  
 34", now 40" D.Fir, S.26°W. 7.3 ft. This tree supposedly destroyed,  
 shows faint bark scribe "S4 T33S".  
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R  
 Office Doug. Co. S 33 | S 34 8  
 1968 Josp. Co. S 3 W  
 New BT: 9" Laurel N. 10° E. 35.7 ft. mkd. T32S R8W S34 SC CS BT.  
 Replaced & Rescbd: 24" D. Fir N.48°W. 13.9 ft. mkd. T32S R8W S33 SC CS BT.

RE-RENEWED, SEE CORNER NO. #116

86

$\frac{1}{4}$  Corner to Section 34 only, T32-8W.  
 Found - No trace of Corner Stone nor N. W. Bearing Tree.  
 5" Corner Tree, now down, shows good scar.  
 8", now 12" D.Fir, N. 31°E. 11.9 ft., scribe visible "SC  $\frac{1}{4}$  34".  
 Set - Brass Cap at  $\frac{1}{4}$  Cor. Mkd: County Surveyor's T 32 S R 8 W  
 Office Doug. Co. S 34 8  
 1968 Josp. Co. T 33 S  
 New BT: 11" D. Fir N. 70° W. 8.1 ft. mkd. SC  $\frac{1}{4}$  S34 CS BT.  
 N. E. Bearing Tree O.K. and tagged.

John M. Powell  
 Frank Jones & W. Penley  
 May, 1968  
 C. S. File No. 54/65