

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T. S. R. 8 W. R. W. W. M.

HOKE-CHAPMAN CO., EUGENE, ORE. 21881

87

Section Corner to Sections 21 - 22 - 27 - 28.
Found - 8", now 16" D. Fir, S.60°E. 9.9 ft. This tree had been
opened but buried in fill od road. Dug out to find
part of "BT". All other trees gone from road construction.
Set - Brass Cap at Sor. Mkd: County Surveyor's T 32 S R 8 W
Office S 21 | S 22
1968 S 28 | S 27
New BT's: 12" Laurel S.35°W. 62.0 ft. mkd. T32S R8W S28 CS BT.
28" D.Fir N.28°W. 42.6 ft. mkd. T32S R8W S21 CS BT.
10" Laurel N. 7° E. 58.5 ft. mkd. T32S R8W S22 CS BT.
Reblzd.&Resrbd: 16" D.Fir S.60°E. 9.9 ft. mkd. T32S R8W S27 CS BT.
Note - This corner lies approx. 60 ft. west of road.

88

1/4 Corner to Sections 26 and 27. See 2007 BLM Resurvey
Found - Orig. 36", now 38" D.Fir, East 15.8 ft., shows old axe work.
Orig. 6" Yew, now down, N.85°W. 6.6 ft., scribe visible "1/4 S".
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 8 W
Office, 1968 1/4 S 27 | S 26
New BT: 8" D.Fir N. 8° E. 56.5 ft. mkd. 1/4 S26 CS BT.
Reblzd. & Resbd: 38" D.Fir East 15.8 ft. mkd. 1/4 S26 CS BT.
Note - No trees in section 27.

89

1/4 Corner to Sections 20 and 21.
Found - Stob of 10" Fir Corner Tree.
16", now 19" D.Fir, S.55°E. 5.9 ft., bark scribe visible "1/4 S BT".
12" D.Fir, now down, N.64°W. 5.9 ft., bark scribe visible "1/4 S BT".
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 8 W
Office, 1968 1/4 S 20 | S 21
New BT: 26" D.Fir N.80W. 18.0 ft. mkd. 1/4 S20 CSBT.
Reblzd. & Resbd: 19" D.Fir S.55°E. 5.9 ft. mkd. 1/4 S21 CS BT.

90

Section Corner to Sections 29 - 30 - 31 - 32.
Found - Orig. BT's.-14", now 36" D.Fir, S.64°E. 6.6 ft., faint bark
scribe " T R8W S BT".
24" Pine, gone, stump hole, S. 44°W. 23.8 ft.
7" D.Fir, now snag, N.28°E. 28.4 ft., shows scar.
No trace of N.W. Orig. BT.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R8 W
Office S 30 | S 29
1968 S 31 | S 32
New BT's: 10" Yew N.59°E. 5.8 ft. mkd. T32S R8W S29 CS BT.
11" Yew N.42°W. 4.0 ft. mkd. T32S R8W S30 CS BT.
24" D.Fir S.56 1/2°W. 69.2 ft. mkd. T32S R8W S31 CS BT.
Reblzd. & Resrbd: 36" D.Fir S.64°E. 6.6 ft. mkd. T32S R8W S32 CSBT.

91

Section Corner to Sections 20 - 21 - 28 - 29.
Found - 1959 Cadastral Brass Cap at Section Corner.
Orig.18", now 30" D.Fir, S.70°W. 38.3 ft., faint bark scribe "S29 R".
Orig.22", now 35" D.Fir, N.5°E.(Rec.N.5°W.) 14.4 ft.(Rec. 15.9')
faint bark scribe "S R T3". New bark scribe "T32 R8W S21 BT".
New BT: 14" Cedar, now 14" N.38°W. 56.0 ft., scribe visible
New BT's: 8" Chinq. S.85°E. 57.4 ft. mkd. T32S R8W S28 CS BT.
Reblzd.&Resrbd: 30" D.Fir S.70°W. 38.3 ft. mkd. T32S R8W S29 CS BT.
Note - This corner lies in fill approx. 20 ft. north of old road.

92

1/4 Corner to Sections 21 and 22.
Found - 36", now 40" D.Fir Corner Tree, faint bark scribe "1/4 S"
on west side.
36", now 40" D.Fir, S.52°W. 32.3 ft., faint bark scribe "1/4 S".
30" Pine, now gone, stump hole, S.40°E. 17.8 ft.
Set - Brass Cap on side of Corner Tree Mkd: County Surveyor's T32S R8W
Office, 1968 1/4 S 21 | S 22
New BT: 14" Laurel S.61°E. 37.3 ft. mkd. 1/4 S22 CS BT.
Reblzd.&Resrbd: 40" D.Fir S.52°W. 32.3 ft. mkd. 1/4 S21 CS BT.

John M. Powell
Frank Jones & W. Penley
May, 1968
C. S. File No. 54/65

RENEWED CORNER NO #107

Dec 30
FD ok
10/19/2
C.S. 6/1/59