

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T. S. R. 8 W. R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

93

1/4 Corner to Sections 29 and 30.
Found - 13", now 24" D. Fir, N. 69° E. 30.4 ft., bark scribe visible "1/4 S".
36" D. Fir, now snag, S. 27° W. 26.4 ft., faint bark scribe "1/4".
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 8 W
Office 1968 1/4 S 30 | S 29
New BT: 42" D. Fir S. 49° W. 42.0 ft. mkd. 1/4 S30 CS BT.
Reblzd. & Rescrbd: 24" D. Fir N. 69° E. 30.4 ft. mkd. 1/4 S29 CS BT.

94

Closing Corner Section 2 & 3, T33-8W. (S. Biry. Sec. 34, T32-8W)
Found - Stone, no marks visible.
14" Laurel S. 40 1/2° W. 59.4 ft., shows good scar.
36" D. Fir, now snag, S. 18° E. 18.5 ft., scribe visible, not legible.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 8 W
Office 1968 Doug. Co. CC S 34
Jos. Co. S 3 | S 2
T 33 S
New BT: 7" D. Fir S. 8° W. 14.6 ft. mkd. T33S R8W S3 CC CS BT.
7" D. Fir S. 71° W. 17.5 ft. mkd. T33S R8W S3 CC CS BT.
No trees to S. E.
Note - This corner lies approx. 295' W. of Sec. Cor. to Secs. 34/35 only,
see Ren. #84. Also about 80' S. of small ravine.

95

Closing Corner to Sections 5 and 6, T33-8W. (S. Biry. Sec. 31, T33-8W)
Found - 15x8x6 Stone at corner, marks visible "C" and grooves.
24" D. Fir, now snag, S. 48° W. 25.1 ft., tree previously opened,
scribe visible "6 CC".
18", now 30" D. Fir, S. 30° E. 15.8 ft., shows good scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's T32S R8W
Office 1968 CC S 31
S 6 | S 5
T33S R8W
New Bearing Object: R.R. Spike in top of 48" Fir Sump S. 41° W. 40.6 ft.
Area logged, no trees. This corner lies on top of ridge, running E-W.

96

Closing Corner Sections 3 and 4, T33-8W. (S. Biry. Sec. 33, T32-8W)
Found - Corner Stone 16x8x6 mkd. 3 notches on E. & W. sides.
36", now 41" D. Fir, S. 13° E. 39.6 ft. shows good face.
48", now 51" D. Fir, S. 62° W. find dist. to be 36.0 ft. & orig. dist.
was 40.9 ft., slope dist. shows good scar. Doug. Co.
Set - Brass Cap at Cor. Mkd: County Surveyor's R8W T32S S 33
Office 1968 T33S S 4 | S 3 CC
Josp. Co.
All trees are in good condition. This corner lies east approx. 125.0
ft. from a spur.

97

SEE CS. 51/68
1/4 Corner Section 35 only, T32-8W.
Found - 18" Pine, now 34", N. 1° W. 42.2 ft., tree opened, "1/4" visible.
36" D. Fir, now 38", N. 55° E. 59.4 ft., shows good scar.
15 x 8 x 6 Stone at 1/4 corner, no marks. Doug. Co.
Set - Brass Cap at Cor. Mkd: County Surveyor's R8W T32S 1/4 S 35
Office 1968 T33S
Jos. Co.

Bearing Trees all O.K., tagged same.

98

Section Corner to Sections 35 & 36, T32-8W.
Found - No Trace of Corner Stone. Larson said he renewed this corner in 1954,
but I do not find any evidence of his corner, See Ren. #2.
Orig. 15", now 20" D. Fir S. 68° E. 23.1 ft., shows good scar.
Orig. 8", now 12" Laurel, S. 52° E. 22.4 ft.
Orig. 15" D. Fir, tree opened N. 24° W. 18.5 ft., scribe marks visible. Doug. Co.
Set - Brass Cap at Cor. Mkd: County Surveyor's R8W T32S 1/4 S 35 | S 36
Office 1968 T33S S 1
Jos. Co.
Bearing Trees O. K., and Tagged.
Note - This corner lies 54.1 ft. E. of the C.C. of Secs. 2/1, T33-8W.
(See Ren. #99)

John M. Powell
Frank Jones & W. Penley
May, 1968
C. S. File No. 54/65