

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 32 S. T. S. R. 8 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97881

99

Closing Corner to Sections 2 and 1, T33-8W.  
Found - 15x10x8 Stone at Sec. Cor. mkd. C.C. on S. face, firmly in place.  
18", now 20" D. Fir, S. 20°W. 25.7 ft. (Rec. 28.4), shows good scar.  
10", now 14" Laurel, S. 23½°E. (Rec. S. 42E) 35.0 ft., shows  
scribing but not legible.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Doug. Co.  
Office R8W T32S S 35  
1968 T33S CC S 2 | S 1  
Jos. Co.  
New BT's: 8" D. Fir S. 89°E. mkd: T33S R8W S1 CC CS BT.  
Note - This corner lies 54.1 ft. W. of Stan. Cor. Secs. 35/36, T32-8W.

100

¼ Corner to Sec. 36, T32-8W.  
Found - Corner Stone 13x14x6, mkd. (SC)  
Orig. 15", now 18" D. Fir, N. 55½°E. 13.9 ft., shows good scar.  
Orig. 18", now 24" D. Fir, N. 62°W. 24.4 ft., open & show scribing.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Doug. Co.  
Office R8W T32S S 36  
1968 R8W T33S ¼  
Jos. Co.  
Rescribed: 24" D. Fir N. 62°W. 24.4 ft. mkd. ¼ S36 SC CS BT.  
Note - This corner lies on S. side of E-W cutting line approx. 85 ft. E.  
of creek.

FD OK 1/6/96 Chaner M123-17

101

Section Corner to Sections 8 - 9 - 16 - 17.  
Found - Orig. 24" D. Fir Corner Tree, now stump, scribing visible,  
"S" "3" & other faint marks.  
36" Pine, now snag, S. 65°W. 16.5 ft., no marks visible.  
No trace of 3 small Laurel BT's.  
Set - Brass Cap on side of Corner Tree Stump Mkd: T 32 S R 8 W  
County Surveyor's S 8 | S 9  
Office, 1968 S 17 | S 16  
New BT's: 7" Tan Oak N. 32°E. 41.6 ft. mkd. T32S R8W S9 CS BT.  
13" D. Fir N. 69½°W. 31.2 ft. mkd. T32S R8W S8 CS BT.  
30" D. Fir S. 36°W. 64.0 ft. mkd. T32S R8W S17 CS BT.  
No trees in S.W. quad. (old unit)

102

¼ Corner to Sections 29 and 32.  
Found - Corner Stone mkd. "¼"  
15", now 20" D. Fir, S. 63°E. 13.2 ft., bark scribe visible, "¼ T".  
14", now 16" D. Fir, N. 54°W. 14.5 ft., bark scribe visible, "¼ B".  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 8 W  
Office ¼ S 29  
1968 ¼ S 32  
Reblzd. & Rescrib: 20" D. Fir S. 63°E. 13.2 ft. mkd. ¼ S32 CS BT.  
16" D. Fir N. 54°W. 14.5 ft. mkd. ¼ S29 CS BT.

103

¼ Corner to Sections 24 and 25.  
Found - 6", now 21" D. Fir, S. 10°W. 15.2 ft., opened for scribe, "¼ S".  
10" Laurel, now dead, rotten, N. 20°W. 21.8 ft.,  
(Both BT's. O.K., good shape, tagged same.)  
Unrecorded BT: 24" D. Fir N. 27°E. 17.4 ft., scribe visible,  
968, also good BT scar.  
Note - This corner lies approx. 60.0 ft. E. of small ravine.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 8 W  
Office ¼ S 24  
1968 ¼ S 25

6/5/68

104

¼ Corner to Sections 22 and 23.  
Found - 10", now 18" Laurel, S. 50°W. 33.7 ft., shows scribing/"BT".  
No trace of S.E. BT.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 8 W  
Office, 1968 ¼ S 22 S 23  
New BT's: 8" Laurel N. 81°E. 9.7 ft., scribed ¼ S23 CS BT.  
26" D. Fir S. 5½°W. 39.6 ft. mkd. ¼ S22 CS BT.  
Note - This ¼ corner lies 220.0 ft. south of a creek approximately.

5/31/68

John M. Powell  
Frank Jones & W. Penley  
May and June, 1968  
C. S. File No. 54/65

RE-RENEWED CORNER NO. #126

RE-RENEWED CORNER NO. #133