

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T. S. R. 8 W. R. W. W. M.

FORE-CHAPMAN CO., EUGENE, ORE. 97501

MARK SMALLEY
ROSEBURG FOREST PROD.
NO 7, 1996
C. 65/15-7

see previous ren# 77

1/4 cor. secs. 15 & 22

132

Mon. FD.- I.P. B.C. - original corner tree crumbling
Bt's Fd.- 8" tan Oak, N.30°W., 40.1', good healed scribe visible
22" Fir, S.30°W., 39.0', good - healed face

New Accessories -

8" Fir, S.71°W., 18.9' scribed "1/4 BT"
5" Fir, N.44°W., 23.8' scribed "1/4 BT"

see previous ren# 104

1/4 cor. secs. 22 & 23

133

Mon. Fd.- 1968 D.C.S.O. I.P.B.C.

Bt's Fd.- 11" Laurel, N.81°E., 9.7' good condition - partially healed face
30" D.Fir, S.5 1/2°W., 39.6' good condition - healed face

New Accessories -

10" Fir, West 41.7' scribed "1/4 S BT"
18" Cedar, N.26°E. 42.6' scribed "1/4 S BT"

Ron Quimby
For: Roseburg
Resources Co.
3/2002
M139-64 A&B

1/4 Secs. 3 & 4

134

Found - BLM brass cap, properly marked.

27" Fir S.3°E, 36.3 ft.

18" Fir (stump) S.82°W, 45.2 Fft.

NEW BTs - 12" Madrone N.83°E, 10.3 ft. (Scribed 1/4 S3 BT)

16" Madrone S.22°W, 20.0 ft. (Scribed 1/4 S3 BT)

1/4 Cor. Secs. 4 & 5

135

Found - BLM brass cap, properly marked.

36" Fir S.10°E, 4.0 ft. (Healed)

18" Fir N.86°W, 44.2 ft. (Healed)

NEW BTs - 10" Fir N.27°W 15.3 ft. scribed: T32S R8W S5 BT

8" Fir S.80°E 23.7 ft. scribed: "X" at breast high
& BT at base.

Richard Templin
For: Fruit
Growers Supply
3/2002
M139-74

Cor. Secs. 8, 9, 16, & 17

136

Found 5/8" iron rod as reported on corner renewal #126.
Previous renewal (#126) states that the "corner is 200 yards
easterly from end of old logging road in sec. 8." This should
state that corner lies 200 ft. Southerly from old logging
road. *SEE Previous Ren for Corner info*

1/4 Cor. Secs. 8 & 9

137

At the proportionate position of the East 1/4 cor. of sec. 8,
I searched for orig. evidence of the 1883 corner with no
success.

At the proportionate position for the 1/4 common to secs. 8 &
9, I set:

A 5/8" x 30" iron rod, projecting 3", with a yellow plastic cap
marked "TEMPLIN LS2359" from which I scribed BTs:

A Madrone, 8" dia., scribed "1/4 S8" "BT" bears N.60°E., 3.1 ft.

A Tan Oak, 6" dia., scribed "1/4 S8" "BT" bears S.3°W., 16.4 ft.

A Tan Oak, 8" dia., scribed "1/4 S8" "BT" bears S.85°W., 22.2 ft.

A D.Fir, 14" dia., scribed "1/4 S8" "BT" bears N.13°W., 12.6 ft.

Corner lies East, 70 ft. from a K-tag on 12" Tan Oak on East
side of road at landing.