

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T. S. R. 9 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

J.M. Powell
&
Crew
C.S.
54/32

Angle Point E. of $\frac{1}{4}$ Corner to Section 2 only, T32-9W. 14
(This A. P. lies 38.0 ft. E. of $\frac{1}{4}$ Cor. Sec. 2 only, T32-9W.
which is a Brass Cap in good condition.)
Found - 18", now 21" D. Fir Corner Tree, opened "AP BT" visible.
28", now 34" D. Fir, S. 77° E. 9.9 ft., shows good scar.
30", now 36" D. Fir S. 87° W. 9.9 ft., shows good scar.
Set - $\frac{3}{4}$ " X 30" Iron Pipe on North Side of Corner Tree.
Note - All BT's. tagged and O. K.

April 26, 1967

Sec. Cor. to Sections 31 and 32 only., T31-9W. 15
Found - 8" Yew, now 9", N. 31° W. 32.6 ft. (Rec. 31.0), faint scribe visible.
8" Yew, N. 16° E. 26.5 ft. (Rec. 25.1) All scribing rotted off.
G.L.O. Brass Cap at Cor., properly mkd. by G.L.O. in 1917
New BT's: 21" D. Fir N. 83° W. 42.5 ft. mkd. T31S R9W S31 CS BT.
38" D. Fir N. 80° E. 42.0 ft. mkd. T31S R9W S32 CS BT.
Note - This cor. lies on steep, N. slope approx. 80.0 ft. S. of small
creek & 660.0 ft. W. of Slide Creek.

$\frac{1}{4}$ Corner to Section 32 only, T31-9W. 16
Found - Brass Cap at Corner properly mkd. by G.L.O. in 1917
Orig. 38" D. Fir S. 78° E. (48° face), shows good scars.
18", now 29" D. Fir Stump, N. 27° E. 109.6 ft., opened for
scribing "3", tree recently logged, opened log.
No trace of 5" Laurel.
New BT's: 12" Pine N. 12° W. 22.4 ft. mkd. $\frac{1}{4}$ S32 CS BT.
13" Pine N. 52° E. 69.3 ft. mkd. $\frac{1}{4}$ S32 CS BT.
Note - This corner lies on top ridge, running approx. N. 20° E. - S. 20° W.

Angle Point East of Sec. Cor. to Sections 6 and 5, T32-9W. 17
(This A.P. lies 349.8 ft. E. of Sec. Cor. to Secs. 6 and 5, T32S, R9W.
Found - G.L.O. Brass Cap properly mkd. in 1917.
36", now 38" D. Fir, N. 11° W. 16.5 ft., shows good scar.
36" D. Fir, now 38", S. 45° W. 11.2 ft., bark scribe visible "T32
"R" "W", broken in half.
New BT: 18" D. Fir S. 26° W. 24.0 ft. mkd. AP CS BT

Angle Point East of Sec. Cor. to Secs. 5 and 4., Twp. Line. 18
Found - This A.P. lies 260.7 ft. E. of Sec. Cor. of Secs. 5 and 4.
G. L. O. Brass Cap at A.P. properly mkd. in 1917.
New BT's: 53" D. Fir S. 58° E. 23.9 ft. mkd. A.P. CS BT.
8" Chinquapin N. 83° W. 29.8 ft. mkd. A.P. CS BT.

$\frac{1}{4}$ Corner to Sections 9 and 16. 19
Found - GLO Brass Cap at $\frac{1}{4}$ Cor., 1917, properly mkd.
5", now 9" Hemlock Stob, N. 85° E. 16.1 ft. (Record 14.5 ft.)
scribe visible "S9 BT".
24" D. Fir, now 30" Stob, S. 72° W. 25.8 ft. (Record 23.8 ft.)
shows scar. 73
New BT's: 14" Hemlock N. 34° E. 11.8 ft. mkd. $\frac{1}{4}$ S 9 CS BT.
16" Hemlock S. 53° E. 12.0 ft. mkd. $\frac{1}{4}$ S16 CS BT.

$\frac{1}{4}$ Corner to Sections 5 and 4. 20
Found - GLO Brass Cap at $\frac{1}{4}$ Cor., 1917, properly marked.
36" D. Fir, now 40" Snag, S. 62° E. 27.1 ft., badly burnt face.
36" D. Fir, now 40" Snag, N. 24° W. 21.1 ft., opened for scribing " $\frac{1}{4}$ ".
New BT's: 5" Laurel N. 38 $\frac{1}{2}$ ° W. 20.7 ft. mkd. $\frac{1}{4}$ CS BT.
5" Chinquapin S. 89° E. 11.6 ft. mkd. $\frac{1}{4}$ CS BT.
Note - No other larger trees available. Corner lies on E. edge of N-S ridge
in burnt & very brushy area. All Trees Tagged.

John M Powell
Frank Jones & J. Brady
May, 1967
C.S. File No. 54/32

John M. Powell
Frank Jones & J. Brady
May, 1967
C. S. File No. 54/44