

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T. S. R. 9 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

50
 $\frac{1}{4}$ Corner to Sections 35 and 36.
 Found - 24" D. Fir, now 27", S. 33° E. 10.6 ft., shows good scar.
 50" S. Pine, now 54", N. 21° W. 31.7 ft., scribe visible "B",
 Tree leaning badly, broken top.
 G.L.O. Brass Cap for $\frac{1}{4}$ corner, properly marked in 1917.
 New BT: 18" D. Fir N. 58° E. 31.0 ft. mkd. $\frac{1}{4}$ S35 CS BT.
 Note - This corner lies 130.0 ft. south of ravine, running N.W.

51
 Section Corner to Section 25 - 26 - 35 - 36.
 Found - G.L.O. Brass Cap at Sec. Cor., properly marked in 1917.
 20" D. Fir, now 22", N. 58° E. 18.5 ft., shows good scar.
 40" D. Fir, now 41", S. 40° E. 30.4 ft., shows good scar.
 36" D. Fir, now down, S. 27° W. 48.2 ft.
 30" D. Fir, now down, N. 74° W. 11.9 ft., shows good scar.
 New BT's: 36" D. Fir N. 55° W. 57.5 ft. mkd. T32S R9W S26 CS BT.
 28" D. Fir S. 68° W. 65.5 ft. mkd. T32S R9W S35 CS BT.

52
 $\frac{1}{4}$ Corner to Sections 26 and 25.
 Found - 6" Laurel, now 9" Stob, S. 62° E. 10.6 ft. mkd. scribe visible.
 60" D. Fir, now 60", N. 42° W. 9.2 ft., shows good scar.
 G.L.O. Brass Cap at $\frac{1}{4}$ Cor. Mkd. properly in 1917
 New BT's: 6" Laurel S. 33° E. 7.0 ft. mkd. $\frac{1}{4}$ S25 CS BT.

53
 $\frac{1}{4}$ Corner to Sections 23 and 24.
 Found - G.L.O. Brass Cap for $\frac{1}{4}$ corner, properly marked in 1917.
 48", now 50" D. Fir, S. 67° E. 33.0 ft., scribe visible "2".
 48" D. Fir, now Stump, N. 57° W. 84.5 ft., scribe visible " $\frac{1}{4}$ 23 BT".
 New BT: 10" Pine S. 62° W. 12.8 ft. mkd. $\frac{1}{4}$ S23 CS BT.
 Note - This corner lies on top of large ridge, running E. & W.

54
 Corner to Sec. 6, T33-8W. & Sec. 1, T33-9W.
 (South Boundary of T.32S.)
 Found - Original 5x8x8 Corner Stone with 4 notches on West side.
 10", now 11" D. Fir, S. 78° E. 30.4 ft., opened & found scribe.
 30", now 36" Pine, S. 30° W. 19.1 ft., shows good face.
 Set - Brass Cap at Sec. Cor. Mkd: County Surveyor's R Doug. Co. R
 Office 9 T32S 8
 1967 W S 1 | S 6 W
 Josp. Co.
 Rescribed: 11" D. Fir S. 78° E. 30.4 ft. mkd. T33S R8W S 6 CS BT.

55
 $\frac{1}{4}$ Corner to Section 25 only, T32-9W.
 Found - GLO Brass Cap at $\frac{1}{4}$ corner, properly marked, 1917
 36", now 39" D. Fir S. 32° W. 67.3 ft., shows good scar.
 8" Chinquapin, now down, N. 18° W. 37.0 ft., rotten
 face shows scribing, "4" 25 BT.
 New BT: 8" Chinquapin N. 89° W. 20.0 ft. mkd. $\frac{1}{4}$ S25 CS BT.

56
 $\frac{1}{4}$ Corner to Section 30 only, T32-8W.
 Found - G.L.O. Brass Cap at $\frac{1}{4}$ corner, properly marked in 1917
 Orig. 40" D. Fir, now stump, S. 80° E. 12.5 ft., shows good scar.
 No trace of N.E. BT.
 New BT: 5" Pine N. 30° E. 6.8 ft. mkd. $\frac{1}{4}$ S30 CS BT.
 7" Pine S. 2° W. 13.5 ft. mkd. $\frac{1}{4}$ S CS BT.
 No larger trees available.

57
 A. P. (Angle Point) South Bdry. of T32-9W.
 Note - This corner lies 126.0 ft. E. of Sec. Cor. to Secs. 35 & 36
 only which is in good condition. All Trees tagged.
 Found - 40", now 45" D. Fir, N. 49° W. 25.7 ft., shows good scar.
 No good evidence of NE. BT., down & rotten.
 G.L.O. Brass Cap at A.P., properly marked in 1917
 New BT: 6" Laurel N. 28 $\frac{1}{2}$ ° E. 13.5 ft. mkd. A. P. CS BT.

John M. Powell
 Frank Jones

June, 1967
 C.S. File No. 54/44