

Douglas County Surveyor's Record of  
Government Corners Renewed

33 T. S. 4 R. W. W. M.

COYE-CHAPMAN CO., EUGENE, ORE. 97196

Witness:  
J. Arkham Jr.  
Geo. Blongren  
July 28, 1954  
Done for Stomar Lmbr.  
Co.  
See C. S. File No.  
41/322.

Section corner to secs. 5, 6, 7 & 8. 1  
Determined by O. B. T.s:  
A 26 inch Y. P. snag bears S. 49° E., 11.0 feet dist. found scribe. #18  
A 38 inch Y. P. bears N. 5° E., 33.0 feet.  
A 16 inch Y. P. bears N. 77° W., 73.0 feet.  
At corner point found stone and made a large pile of stones.  
From Which:  
A 10 inch Y. P. bears S. 5° W., 12.0 feet dist., mkd. S 7, BT.  
A 9 inch Fir bears S. 45° E., 20.0 feet dist., mkd. S 8 BT.  
Corner lies on top of ridge at the east end of rocky opening.

H. W. Lawrence  
August, 1955  
C. S. File No. 42/79.

1/4 corner to secs. 7 and 8. 2  
Corner set at mid point on line between section corners.  
Set a 3/4 inch o. d. galv. iron pipe, 36 inches long set in the ground  
with a mound of stone 18 inches high surrounding the pipe,  
from which:  
A R. fir, 30 inches in dia. bears N. 34° E., 31.4 feet dist. #16  
bark scribed 1/4 S 8 B T 1543.  
A R. fir, 18 inches in dia. bears S. 29° W., 41.6 feet dist.  
scribed 1/4 S 7 B T 1543.  
Some one, unknown to me placed a stake witnessed by a fir tree  
marked 1/4 cor. at 15.3 feet N. and 42 feet W. of the corner I set. Cut  
brush indicates he came in from the east.

S. W. Corner to Section 31. - 732-4W 3  
(on E. & N. lines of Sec. 1. T 33 SR 5 W)  
Found - Doug. Fir (now 21" diam.) N. 47° E. 21.1 ft. Fragmentary  
scribing visible on partially rotted face. Did not find  
marked rock at corner.  
Set - Brass Cap mkd: "County Surveyor's Office 1964  
T 32 S " Erect rock mound around pipe.  
R S 31 R  
5 S 1 4  
W W  
T 33 S  
Rescribe: 21" Doug. Fir N. 47° E. 21.1 ft. Mkd: "T 32 SR 4 W S 31 CS BT"  
New BT: 9" Doug. Fir S. 44° E. 11.2 ft. Mkd: "T 33 SR 5 W S 1 CS BT"  
Corner lies on very rock, very steep, NW slope.

Milo E. Godfrey, Dep. Surv.  
Win. Stoffel, Mike Darby, Mike Stone  
June, 1964  
C. S. File No. 53/52

Corner to Sections 1 & 36. 4  
(on W. line Sec. 31 T. 32 S.R. 4 W.)  
Found - Doug. Fir (now 24" diam.) S. 60° W. 11.2 ft. Scribing visible  
on partly exposed face "R 5 W"-tree alive & in good  
condition.  
Doug. Fir (now 23" diam.) N. 62° W. 13.2 ft. Previously  
opened, but nearly healed over-now scribing visible-tree in  
good condition  
Doug. Fir (now 26" diam.) N. 42° E. 21.8 ft. (now 17.8 ft)-  
scribing visible on partially exposed face "S31"-tree in  
good condtion.  
Partly rotten cedar stump S. 58° E. 25.7 ft. Scribing visible  
"R 4 W T 33 S S 6"  
Set - Brass Cap Mkd: "County Surveyor's Office 1964  
T 32 S "  
R S 36 S R  
5 S 1 31 4  
W W  
T 33 S  
Did not mark any new trees.