

Douglas County Surveyor's Record of
Government Corners Renewed

T. 33 S. T. S. R. 4 W. R. W. W. M.

KOKE-CHARMAN CO., EUGENE, ORE. 21891

John M. Powell
W. Penley and J. Heritage
C. S. File No. 54/114

Standard $\frac{1}{4}$ Corner to Section 33, T32-4W. 10
Found - 12" Cedar (Rec. Fir), now 20", S.50°W. 16.5 ft., opened for
scribe. (Ring Count places age approx. 1885)
6" Fir, down-rotten, N.45°W. 4.0 ft., has very old rotten
face, maybe very faint scribe.
Set - Brass Cap at Cor. Mkd: County Surveyor's T32S R4W Doug. Co.
Office T33S S 33
1970 S $\frac{1}{4}$ C Jack. Co.

New BT's: 38" D. Fir N.52°E. 15.6 ft. mkd: "S $\frac{1}{4}$ C S33 CS BT".
12" D. Fir N.38°W. 12.7 ft. mkd: "S $\frac{1}{4}$ C S33 CS BT".
By pacing, corner hits approx. 9 chains W. of CC S33/S34 and
3 chains east of ridge.

5/14/70

Standard $\frac{1}{4}$ Corner to Sections 32, T32-4W. 11
Found - 16", now 24" Cedar, S.45°E. 16.5 ft., opened for scribe,
burnt & rotted face, but found definite reverse scribing.
20" D. Fir, now stump, N.68°W. 6.6 ft., no marks found.
Set - Brass Cap at Cor. Mkd: County Surveyor's T32S R4W S $\frac{1}{4}$ C S 32
Office, 1970 T33S Jack. Co.

New BT's: 14" D. Fir N.15°W. 30.6 ft. mkd: "S $\frac{1}{4}$ C S 32 CS BT".
8" D. Fir S.61°E. 18.4 ft. mkd: "S $\frac{1}{4}$ C CS BT".

5/15/70

Standard Section Corner to Sections 33 and 34, T32-4W. 12
Found - No trace of N.W. BT.
18" D. Fir, now dead stob, N.45°E. 12.5 ft., upper face
open, old rotten scribe visible, "S" & other marks.
Set - Brass Cap at Cor. Mkd: County Surveyor's T32S R4W S 33 | S 34
Office T33S S SC Jack. Co.
1970

New BT's: 24" D. Fir N.48°E. 19.5 ft. mkd: "T32S R4W S SC S34 CS BT".
32" D. Fir N. 8°W. 21.4 ft. mkd: "T32S R4W S SC S33 CS BT".
This corner lies approx. 125.0 ft. west of draw.

5/19/70

Section Corner to Sections 4 - 5 - 8 - 9. 13
Found - 1962 Cadastral Brass Cap, properly set & mkd:
Orig. 21" D. Fir, alive, S.60°E. 15.2 ft., shows good scar. *FD. OK 6/19*
Orig. 28" D. Fir Alive, N.30°E. 16.5 ft., shows good scar. *8cm C.S. 58/202*
Orig. 16" D. Fir Snag, dead, S.50°W. 47.5 ft., shows scar & has been opened.
12" R. Fir Alive, N.59°W. 52.8 ft. scribe visible on nearly healed blaze.
New BT: 11" R. Fir S.50°W. 29.2 ft. mkd: "T33S R4W S 8 DCS BT".
From this corner a mound of stone 2 ft. at the base, 1 ft. high, bears
N.13 $\frac{1}{2}$ °W. 10.4 ft. and a mound of stone 1 $\frac{1}{2}$ ft. at the base & 1 ft. high
bears N.71°E. 10.7 ft.

6/4/70

$\frac{1}{4}$ Corner to Sections 4 and 5. 14
Found - Basalt Corner Stone, in place & mkd: " $\frac{1}{4}$ " as called for.
Orig. 14", now 18" Fir, alive, N.23°W. 23.1 ft., prev. opened,
scribe visible on burned blaze.
Orig. 18", now 19" Cedar, alive, S.45°E. 38.9 ft., prev. opened
and scribe visible. *FD. OK 6/19*
8cm
Set - Brass Cap at Cor. Mkd: County Surveyor's T 33 S R 4 W
(Reset old Stone alongside) Office Doug. $\frac{1}{4}$ S 5 | S 4 Jack.
1970 Co. Co. C. S.
58/202

New BT's: 22" D. Fir S.82°W. 23.7 ft. mkd: " $\frac{1}{4}$ S5 DCS BT".
14" Cedar N.21°E. 36.4 ft. mkd: " $\frac{1}{4}$ S4 DCS BT".
This corner lies on moderate N.W. slope.

6/4/70

$\frac{1}{4}$ Corner to Sections 5 and 6. 15
Found - 24x10x10 Stone mkd: "4", lying in mound of stone with "4" on E. face.
18", now 24" Pine, N.73°E. (Rec. N66E) 64.7 ft., tree opened earlier "S" visible
24" Pine, now snag, S1 $\frac{1}{2}$ °E. (Rec. 52W) 47.5 ft. scribe visible, " $\frac{1}{4}$ S BT".
Counting rings of N.E. BT. shows tree old enough for Orig. BT. Call of
1 chain is good to top of ridge. Renew by intersection of distance of BT's.
as there is a lot of local attraction in area.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 33 S R 4 W
(Set in Mound of Stone) Office, 1970 $\frac{1}{4}$ S 6 | S 5 Jack.
Co. C. S.

New BT: 10" Pine N.31°W. 9.7 ft. mkd: " $\frac{1}{4}$ S 6 CS BT".

6/4/70