

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 33 S. T. S. R. 4 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORG. 21881

1/4 Corner to Sections 7 and 8.

Found - 3/4" I. Pipe at corner in mound of stone, See Ren. #2.

30" D. Fir, now stump, N. 34° E. 31.4 ft., bark scribe visible (1543)

18", now 20" D. Fir, S. 29° W. 41.6 ft., shows good scar.

Set - Brass Cap at Cor. Mkd: County Surveyor's D T 33 S R 4 W

Office 1970  
g o; S 7 S 8 Jack. Co.

New BT: 15" W. Fir N. 73° E. 3.7 ft. mkd: "1/4 S 8 CS BT".

6/5/70

1/4 Corner to Sections 5 and 8.

Found - Stone 15x8x6 mkd: "1/4" on North.

9", now 22" Cedar, N. 55° E. 20.4 ft., shows good scar.

24", now 36" D. Fir, S. 38° W. 14.5 ft. shows good scar.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 33 S R 4 W

Office 1970  
1/4 S 5 S 8 - Doug. Co. Jack. Co.

New BT: 6" Cedar S. 70° W. 15.7 ft. mkd: "1/4 S 8 DCSBT".

6/4/70

Section Corner to Sections 6 - 5 - 7 - 8.

Found - 18x10x8 Stone, firmly set, mkd: with notches on N. & S. sides.

Orig. 24", now 30" Y. Pine, N. 5° E. 33.0 ft., shows good scar. See Ren. #1.

Orig. 24" Y. Pine, now snag, S. 56° E. (Rec. S49E) 11.2 ft. scribe visible.

Orig. 12", now 15" Y. Pine, N. 55° W. 75.2 ft. (Rec. 77.2) Orig. dist.

may be slope distance.

9", now 9" D. Fir, S. 45° E. 21.3 ft. (Rec. S45E 20.0), shows good scar.

10", now 11" Y. Pine, S. 2 1/2° W. 12.7 ft. (Rec. S5W 12.0) parts of scribe marks visible.

Set - Brass Cap at Cor. mkd: County Surveyor's T 33 S R 4 W

Office 1970  
S 6 S 5 S 7 S 8

All Bearing Trees 0. K. and Tagged.

This corner lies on very rocky ridge at E. end of opening.

6/4/70

1/4 Corner to Sections 7 and 18.

Found - 5" Yew Corner Tree, now down & rotted, scribe visible, "1/4 S".

Orig. 6", now 17" W. Fir, S. 45° E. 10.0 ft. (Rec. 15.8), shows good scar.

8" W. Fir N. 22 1/2° W. 23.1 ft., scribed "1/4 S 7 BT".

1968 B. L. M. Brass Cap at 1/4 Corner, properly marked.

Rebzd. & Resbd: 17" W. Fir S. 45° E. 10.0 ft. mkd: "1/4 S 18 CS BT".

6/5/70

Section Corner to Sections 7 - 8 - 17 - 18.

Found - Cadastral Brass Cap, 1962, alongside Corner Stone.

8" N. Fir S. 47 1/2° W. 61.4 ft., shows good scar.

10" N. Fir N. 23 1/2° W. 22.4 ft., shows good scar.

6" N. Fir N. 36° E. 39.3 ft. (Rec. 34.2) bark scribed "T33S R4W S8 BT".

26" D. Fir S. 42° E. 11.9 ft., This tree cut open, scribe visible.

(Dead Top)

New BT: 36" N. Fir S. 65° E. 30.2 ft. mkd: T33S R4W S17 CS BT".

6/5/70

Cl. Cor. to Secs. 32 & 33, T32-4W.

Found - No trace of Stone Monument.

14", now 21" D. Fir, N. 18° E. 20.5 ft., scribing vis. on burnt face.

24", now 30" D. Fir, N. 17° W. 16.5 ft., shows good scar. O.K.

Set - Brass Cap at Cor. Mkd: County Surveyor's T32S R4W CC S 32 | S 33

Office, 1970 T33S S 5

Rblzd. & Resbd: 21" D. Fir N. 18° E. 20.5 ft. mkd: "T32SR4W CC S33 CS BT"

5/19/70

Standard 1/4 Cor. to Sec. 31, T32-4W.

Found - 18" D. Fir, now stob, N. 30° W. 15.7 ft. (Rec. N30E 12.9) scribe vis.

18" D. Fir, now stob, S. 27° W. 11.9 ft., scribe visible.

By facing up trees, assume S. tree correct, Also hit old E-W blzd. line.

Set - Brass Cap at Cor. Mkd: County Surveyor's T32S R4W S 31

Office, 1970 T33S R4W S 1/4 C

New BT's: 6" D. Fir N. 39° E. 12.5 ft. mkd: "S 1/4 C S31 CS BT".

Old mound of stones is 1.5 ft., not called for in notes, but look like they were put there.

16

17

18

19

20A

#21

FD OK DIESKE M117-13 5/93

FD OK 6/79 BLM C.S. 58/202

FD OK DIESKE M117-13 5-93

FD OK PIGSKE M117-13 5/93

FD OK 6/79 820 SEE C.S. 58/202

John M. Powell  
W. Penley and J. Heritage  
C. S. File No. 54/114

1-79  
MARCH 71