

Douglas County Surveyor's Record of  
Government Corners Renewed

33 T. S. 5 R. W. W. M.

KOYE-CHAPMAN CO., EUGENE, ORE. 97196

CLOSING SEC. COR. SECS. 1 and 2  
Location identified from O.B.T.s as described in government field notes.

**RE-RENEWED, SEE CORNER NO. #38**

12" Fir S 44° E 61 lks.  
12" Fir N 85° E 54 lks.  
Pine S 30° W cut for wood but scribe marks visible on stump.  
Blazed and scribed for new B.T.  
12" Fir S 32° W 46 lks. T 33 S R 5 W S 2 CSBT.  
C.O. Garrett had driven a 1 1/2" I.P. for corner.  
All O.B.T.s reblazed and scribed.

CLOSING SEC. COR. SECS. 2 and 3

A rock 6" x 8" x 6" above ground original corner as described.  
O.B.T.s in good condition as follows:  
8" Fir (now 12") N 70° E 33 lks.  
12" Fir S 62° E 8 lks  
8" Madrone (now 12") S 68° W 8 lks.  
I reblaze and scribe all B.T.s

CLOSING 1/4 SEC. COR. SEC. 2

Placed on township line midway between Section Corners. Drove 1 1/4" x 42" I.P. 36" in ground for corner. 6" x 8" x 60" Yew wood post alongside scribed CC 1/4 S 2 on South face and C S on North face.  
20" Fir South 73 lks. blazed and scribed CC 1/4 S 2 CSBT.  
20" Fir S 58° E 64 lks. " " " " " " " " 20

1/4 SEC. COR. SECS. 1 and 2.

Rock (serpentine not basaltic) as called for in govt. field notes.  
O.B.T.s alive and in excellent shape.  
30" Sugar Pine N 41° W 39 lks.  
10" Fir S 39° 30' E 91 lks.

1/4 SEC. COR. SECS. 2 - 11

5" x 8" x 6" above ground granite boulder as described in govt. field notes. O.B.T.s in excellent condition, one having been chopped out scribe marks legible. Reblazed and scribed in bark both trees.  
24" Fir (now 32") N 27° 30' E 53 lks.  
24" Fir (now 32") S 41° W 44 lks.

1/4 SEC. COR. SECS. 2 - 3

6" x 12" x 6" above ground slate (or schist) stone as described in govt. field notes. B.T.s in good condition, did not chop out, but reblazed and scribed.  
12" Fir (now 18") N 30° 45' E 149 lks.  
30" Sugar Pine (now 36") S 36° 30' W 112 lks.

Closing section corner to secs. 3 and 4.

This corner bears South 5 1/2 lks. dist., from the sec. line between 3 and 4 on the south and sec 33 on the North and is monumented with a basalt stone, 10x8x5 ins. above ground, firmly set, mkd. CC on S., with 3 grooves on E and W. faces; from which the orig. B. T.s:  
A Douglas Fir, 24 ins. diam., bears S. 48 1/2° E., 210 lks. dist. with old blaze healed.  
A Douglas Fir stub, 30 ins. diam., bears S. 43° W., 70 1/2 lks. dist., mkd. with old blaze healed.  
Against the north side of the stone, Set an iron pipe, 3 feet long, 2 ins. diam., 28 ins. in the ground, mkd., RS33 and mark new bearing trees as follows:  
A Douglas Fir, 12 ins. diam., bears S. 12 1/4° E., 26 lks. dist., Mkd. T33S R5W S3 RS33CC BT.  
A Douglas Fir, 16 ins. diam., bears S. 29° W., 17 1/2 lks. dist., mkd. mkd. T33S R5W S4 RS33 CC BT.

1/4 corner on North boundary of section 4.

This corner lies mid point between the two North closing corners of Section 4 and 46.22 Chains from each one.  
Set an iron pipe, 3 feet long, 1 1/2 ins. diam., 28 ins. in the ground, mkd. RS33 from which:  
(over, on next page)

BEN. B. IRVING  
JUNE 1930  
C.S. 46/109

C.S. 37/23  
RM 1-11-BB.I

Norman D. Price - July 27 - 28, 1953  
Survey for the Dollar and Patterson Lumber Co.  
Filed in File 41, Envelope 184

**RE-RENEWED, SEE CORNER NO. 4-11-67 CORNER VISITED, O.K. J.M.P.**

9-11-67 - CORNER O.K. J.M.P.