

Douglas County Surveyor's Record of
Government Corners Renewed

33 T. S. 5 R. W. W. M.

KORF-CHAPMAN CO., EUGENE, ORE. 97195

(continued from last page)

A Douglas Fir, 14 ins. diam., bears S. $53\frac{1}{2}^{\circ}$ E., 56 lks. dist., mkd. $\frac{1}{4}$ S4 RS33 BT.
A Douglas Fir, 24 ins. diam., bears S. 21° W., 43 lks. dist., mkd. $\frac{1}{4}$ S4 RS33 BT.

See preceding page.

$\frac{1}{4}$ corner of secs 11 and 12. 10
A granite stone 10x8 ins., firmly set flush with top of ground, mkd $\frac{1}{4}$ on W. face; from which the original bearing trees:
A Douglas Fir, 36 ins. diam., bears S. 54° E., 18 feet dist., with blaze healed.
An incense cedar, 18 ins. diam., bears N. $23\frac{1}{2}^{\circ}$ W., 22.4 feet dist., with scribe marks $\frac{1}{4}$ S uncovered.
Against N. side of stone, set an iron pipe, 3 feet long, $1\frac{1}{4}$ ins. diam., 28 ins. in the ground, mkd. RS33.

Norman D. Price
July 1953
In file 41,
env. 184

$\frac{1}{4}$ sec. corner to secs. 1 and 2. 11
 $1\frac{1}{4}$ inch Iron pipe.
From which:
30 inch Pine, N. 41° W., 25.7 feet.
10 inch Fir, S. $39^{\circ}30'$ E., 60.0 feet.

Ren. #4

Geo. J. Wenderoth
1955.
C. S. File 46/109;

Closing Corner for Sections 5 & 6. 12
Found - Stone at Corner as recorded, except I do not find the "CC".
Orig. 36", now 40" Fir Stump S. 55° E. 40.9 ft. I open & find good scribing "R5W".
Orig. 30", now 36" Fir N. 38° E. 17.2 ft. Shows good scar, I do not open.
Set Brass Cap at Corner Mkd: County Surveyor's Office, 1958
$$\begin{array}{c} \text{S } 6 \text{ | } \text{S } 5 \\ \hline \end{array}$$

New BT's: 24" Fir bears S. 12° E. 18.0 ft. scribed T33S R5W CC S5 CS BT
6" Acorn Oak S. 44° W. 12.2 ft. scribed T33S R5W CC S6 CS BT

James W. Byron, Deputy Surveyor
Milo Godfrey
S. A. Bilow
Aug. 19, 1958
For C. & D. Lumber Co.
C. S. File No. 49/112
M 12 - 51

North $\frac{1}{4}$ Corner Section 6. 13 Set by proportion.
Set Brass Cap at Corner Mkd: North $\frac{1}{4}$ S6 T33S R5W County Surveyor's Office, 1958
BT's: 14" R. Fir bears S. 78° W. 20.5 ft. scribed $\frac{1}{4}$ S6 CS BT.
8" Laurel bears S 40° E. 10.5 ft. scribed $\frac{1}{4}$ S6 CS BT.

Renewed Corner to Secs. T32S R6W $\frac{S36/S31}{S1}$ R5W 14
Found - $1\frac{1}{4}$ " Axle at Corner & Large Fir Stump S. 37° W. 45.5 feet.
New BT's: 8" R. Fir N. $3^{\circ}30'$ W. 15.4 feet. (scribed by RE 3024)-3/19/68, Revisited)
40" R. Fir N. 7° E. 42.0 feet. (this corner, fd. as recorded-Call to Ck)
(to W. checks record.-Find 23" Laurel, center fotted, checks for N.E. BT.) Addn. notes in 14-A (file)

South $\frac{1}{4}$ Corner to Section 31 only, T32S R5W.
Set by Proportion - Set Brass Cap at Cor. Mkd: County Surveyor's Office, 1958
South $\frac{1}{4}$ S31, T32S R5W.
New BT's: 10" R. Fir bears N. 37° E. 3.5 ft. scribed $\frac{1}{4}$ S31 CS BT.
10" Laurel bears N. $27^{\circ}30'$ W. 33.2 ft. scribed $\frac{1}{4}$ S31 CS BT.

James W. Byron, Deputy
For D. & D. Lumber
August 1958
C. S. File No. 49/112
Map File M 12 - 51

Sec. Cor. to Secs. 31 and 32 only, T32S R5W. 14-B
Found - Pipe at Cor. & all BT's. Set - Brass Cap at Corner Mkd: County Surveyor's Office, 1958 $\frac{S31/S32}{S5}$ T32S R5W
New BT: 5" W. Fir S. 65° W. 11.6 ft. scribed CC S31-S32 CS BT.
Note - Destroyed all evidence of Standard Corner.