

Douglas County Surveyor's Record of
Government Corners Renewed

T. 33 S. T. S. R. 5 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97101

19

Closing Corner to Sections 5 and 4.

Found - Bedrail at the approx. corner is N. 54° E. 6.4 ft. from corner.
48" D. Fir, now 56" Stump S. 34½° E. 87.1 ft., shows scribing
of "T".

No trace of other bearing trees.

Set - Brass Cap at C.C. Cor. Mkd: County Surveyor's
Office
1967

T 32 S
S 5 | S 4
T 33 S R5W

New BT's: 8" Hemlock S. 78° W. 28.5 ft. mkd. T33S R5W S5 CS BT.
10" Hemlock S. 21° E. 35.0 ft. mkd. T33S R5W S4 CS BT.

Note - This corner lies in middle of old cat road & 40' W. of small ck.
(Believe Bedrail was moved from position used by Price) July 26, 1967
(See C. S. File No 41/184 & C.S. 53/52)

20

½ Corner to Section 2 only, T33-5W.

Found - 1½" I. Pipe, 1 ft. underground & wooden stake scribed CC ½ S2 CS.
Ren. #3.

20" D. Fir, now 24" Stump, South 48.1 ft., opened for scribe.
39" D. Fir S. 58° E. 42.2 ft., shows good scar.

Set - Brass Cap at Cor. Mkd: County Surveyors
Office
1967

T 32 S R5 W
S 2 T33S

New BT: 8" Laurel S. 69° W. 15.6 ft. mkd. ½ S 2 CS BT.

Note - This corner lies at fence corner, running S. and E.

21

½ Corner to Sections 6 and 5.

Found - Orig. 40" D. Fir, now 48" Stump, S. 19° W. 36.3 ft., stump had
been opened, scribe visible "½ S".

Orig. 18" D. Fir, now rotten stump, N. 17° E. 59.4 ft.

No trace of Corner Stone.

Set - Brass Cap at ¼ Cor. Mkd: County Surveyors
Office, 1967

T 33 S R 5 W
½ S 6 | S 5

New BT's: 12" D. Fir S. 19° W. 2.8 ft. mkd. ½ S 6 CS BT.

13" D. Fir S. 44½° E. 15.6 ft. mkd. ½ S 5 CS BT.

22

Closing Corner to Sections 35 and 36.

Found - 16", now 34" D. Fir, N. 21° E. 39.6 ft., tree had been
opened, scribe visible, "T32S".

40", now 45" Pine, N. 81° W. 38.3 ft.

Set - Brass Cap at Cor. Mkd: County Surveyors
Office
1967

T 32 S R 5 W
S 35 | S 36
S 1

New BT's: 9" Laurel N. 31° W. 8.3 ft. mkd. CC T32S R5W S35 CS BT.

11" D. Fir N. 17° E. 8.3 ft. mkd. CC T32S R5W S36 CS BT.

Note - This corner lies east of A. P. (7) 1965 351.7 ft.

23

Closing Corner to Sections 3 and 2, T33-5W.

Found - 6x8x6 Corner Stone mkd. "CC". See Ren. #2, T33-5W.

12", now 18" D. Fir, N. 70° E. 21.8 ft., shows bark scribing,
"T32S R5W BT", plus a good original face.

12" D. Fir, now 16" Stump, S. 62° E. 22.4 ft., shows good
bark scribe of "T33S R5W".

Set - Brass Cap at C.C. mkd: County Surveyor
(Set beside Cor. Stone) Office
1967

T 32 S R 5 W
C C
S 3 | S 2
T 33 S R 5 W

New BT's: 28" D. Fir S. 28° W. 31.9 ft. mkd. T33S R5W S3 CC CS BT.

22" Dedar S. 7° E. 49.0 ft. mkd. T33S R5W S2 CC CS BT.

John M.
Powell &
Crew
7/26/67
C.S. File
No.
53/52

John M. Powell
Frank Jones & Joe Brady
August, 1967
C.S. File No. 53/52

RE-RENEWED, SEE CORNER NO. #36

Fl. o.k. by:
L.D. SMITH
MAY 14, 1982
M 92-34

FD. OK 8/93, BENTZ
1993-0078