

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 33 S. T. S. R. 5 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

30

1/4 Corner to Section 6, T33-5W. & Section 1, T33-6W.  
Bound - Orig. 14" B.Oak, now stump, S.34°W. (Rec. S32W) 31.7 ft.,  
opened for scribe "BT".  
Orig. 12", now 23" B.Oak, S.60°E. 8.6 ft., shows scar.

Set - Brass Cap at Cor. Mkd: County Surveyor's Douglas Co.  
Office R T 33 S R  
1968 6 1/4 S 1 S 6 -5  
W Jos. Co. W

New BT: 11" D.Fir S.31°W. 24.3 ft. mkd. 1/4 S1 CS BT.  
Reblzd. & Resc'd: 23" B.Oak S.60°E. 8.6 ft. mkd. 1/4 S6 CS BT.  
Note - Corner lies approx. 35.0 ft. S. of ridge top, ridge running E-W.

3/19/68

31

Witness corner, Corner 2, Mineral survey #920 "Hard Times Lode"  
Found - An orig. 16" D. Fir, now a 17" stump bears S.30 1/4°W., 49.4 ft.  
with traces of scribing visible along the edges of an un-  
healed blaze. It appears as if the scribing has been chopped  
out.

An orig. 20" Fir, now a 24" snag, bears S.63°W., 48.5 ft. with  
no marks visible on an unhealed blaze.

The orig. monument is gone.

An unrecorded 3/8" Iron rod, bears S.78°E., 1.3 ft.

Due to impending road construction in the area, we do not monument the  
true corner point.

WE SET: A witness corner as follows:

At a point 60.0 ft. east of the true corner point, we set a  
1" x 30" Iron pipe 28" in the ground for the witness cor.  
with brass cap attached, stamped:

Douglas Co. Surveyor  
T 33 S R 5 W  
Witness Cor.  
MS  
Cor. 2 920  
West 60 ft. to  
True Cor.  
1976

New BT's- A 26" D.Fir, bears N.75°E., 24.8 ft. scribed "WC HT 2 920  
CS BT" on a double blaze.

A 12" Madrone, bears S.21°W., 9.5 ft. scribed "WC HT 2 920  
CS BT" on a double blaze.

10/12/76

32

Hard Times Lode Survey #920, Corner #1

Found - A diorite stone 28"x10"x8", 18" in ground and in a mound of  
stone. The corner stone was marked "HT-1-920"

From Which:

An orig. 6" Yew, bears S.58 1/4°E., 29.0 ft. Tree is alive  
and shows scribing

A 60" Incense Cedar stump bears S.0°30'E., 9.0 ft. stump shows  
scribing.

New BT's- A 7" Madrone bears S.67°E., 9.2 ft. mkd. "HT-1-920 CS BT"  
in a double blaze.

We do not set brass cap as orig. stone is well mkd. as per record and con-  
sidering it's size, depth in ground, the mound of stone surrounding it,  
and it's structural integrity, I believe it to be superior to a brass cap  
as a permanent monument.

10/14/76

33

Hard Times Lode Survey #920, Corner #3.

Found - A Basalt stone 20" x 12" x 8", 4" in ground (Rec. 24"x14"x8",  
16" in ground) marked "HT 3 - 920"

A 28" D. Fir, (now 34" bears S.35°W., 55.5 ft. (rec. S.38°W.,)  
No blaze.

A 16" Sugar Pine (now 24") bears S.85°W., 23.4 ft. (rec. S.89 1/2°W.,  
24.6 ft.) No blaze.

The two above trees have no apparent blazes or scribing as called for in the  
record "HT 3 920 BT"

Set - A 1" x 30" Gal. I.P. with brass cap 25" in ground mkd:  
Douglas Co. Surveyor T 33 S R 5 W

Cor. MS  
3 | > 920  
1976

James W. Byron  
J.M. Powell & Crew  
3/19/68  
C.S. File No. 49/112

MARCH 71

Gary L. Langlitz Doug. Co. Surveyors Off  
Karen Cheney  
Oct. 12, 1976  
C.S. 59/24

Gary L. Langlitz, Doug. Co. Surveyors OF  
K. Cheney  
Oct. 14, 1976  
C.S. 59/24