

Douglas County Surveyor's Record of  
Government Corners Renewed

T 33 S. T. S. R 6 W R. W. W. M.

FOKE-CHAPMAN CO., EUGENE, ORE., 21881

17

1/4 Corner North Side of Sec. 4, T33-6W.  
Corner Washed away - Found the 12" Maple S.21°E. 27.1 ft. for the  
1/4 corner, the only tree left. *Ren. #6*

Set - 1" I. Pipe 38.8 ft. West on WNW. Line.

Scribed: 26" Maple S.35°04'W. 33.1 ft.

12" Maple S.32°45'E. 31.6 ft.

Set - 1" I. Pipe 76.8 ft. South on Centerline Sec. 4. - *Wir. Cor.*

Scribed 36" Maple S.27°06'E. 76.5 ft.

36" Cedar S.58°05'W. 84.4 ft.

FOUND O.K. 10-3-67 J.M.P.

1/4 Corner between Sections 4 and 9.

Found - 56" Pine N.54°E. 21.8 ft., only stump remains.

Iron Rod with pulley on top 5 ft. North of bearing & distance.

Set - 1" I. Pipe at Corner.

Scribed - 7" Chinquapin N.2°05'E. 33.7 ft.

5" Madrona N.64°43'E. 32.0 ft.

1/2 Corner between Sections 4 and 5.

Found - 2" I.P. and remains of old Bearing Trees. *REN. #4*

Scribed - 18" Fir S.41°04'E. 29.8 ft.

12" Alder S.32°20'W. 35.5 ft.

FOUND O.K. - OCT. 1967

FD 1/8" M. HULL M 76-75: 4/8" Rm-3-61

Center of Section 4.

(2698.1 ft. S. of N 1/4 Cor.)

(2643.3 ft. E. of W 1/4 Cor.)

Set - 1" I. Pipe

Scribed - 14" Madrona N.9°18'E. 42.7 ft.

13" Madrona S.43°50'E. 28.0 ft.

Section Corner to Sections 5 - 6 - 7 - 8.

Found - Rotted Stump Section of Orig. 14" Laurel S.10°W. 6.6 ft.,  
shows reverse scribe marks

No other Original Bearing Trees found.

Call North to Creek checks O. K.

Fine new 2" x 2" Stake & mound of Rocks at corner.

Set - Brass Cap at Cor. Mkd: County Surveyor's 

S 6	S 5
S 7	S 8

 T33S R6W

New BT's: 8" Laurel bears S.20°W. 7.5 ft. scribed S7 T33S R6W CS BT.

8" Laurel bears S.10°E. 8.2 ft. scribed S8 T33S R6W CS BT.

9" R. Fir bears S.80°E. 76.9 ft. scribed S8 T33S R6W CS BT.

No trees near to NE. or N.W.

Section Corner to Sections 7 - 8 - 17 - 18.

Found - Orig. 20", now 34" Fir Snag N.52°W. 18.1 ft., no scribing.

Orig. 20", now 30" Fir Snag N.46°E. 14.5 ft., shows old axe marks.

Orig. 14", now 16" Laurel Snag, shows old rotted face & axe work.

No scribing found.

Stump hole for Original S.W. Bearing Tree.

Note - This is in old burn area. The Firs were probably bark scribed.

Ring count checks for size & all check record bearing & distance.

Set - Brass Cap at Cor. Mkd: County Surveyor's 

S 7	S 8
S 18	S 17

 T33S R6W

New BT's: 6" Chinq. bears S.7°E. 7.9 ft. scribed S17 T33S R6W CS BT.

11" Laurel bears S.75°W. 35.2 ft. scribed S18 T33S R6W CS BT.

3" Fir bears N.70°W. 20.0 ft. scribed CS BT.

5" R. Fir bears N.29°E. 20.4 ft. scribed S8 CS BT.

GEORGE J. WENDEROTH  
Survey for O. Miller & L. Coate  
December 31, 1962  
C.S. File No. 52/137  
Map File M 24 - 44

James W.  
Byron & Crew  
Feb. 14, 1963  
C. S. File  
No. 53/8

James W.  
Byron and  
Crew  
July 2,  
1963  
C.S. File  
No. 53/8

RE-RENEWED SEE CORNER NO. #53

RE-RENEWED SEE CORNER NO. 51

FD OK BY G. NYGREN  
3/94 M 118-79

FD OK  
1/18/64  
2. Thom person  
RM 3-61