

Douglas County Surveyor's Record of
Government Corners Renewed

T 33 T. S. R 6 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97501

57

Section Corner for Secs. 35 and 36 only of T.32-6

Found - 1" iron pipe projecting 6" above ground Ren. #34
46" fir bears N.56°W., (N.40°W), 9.0 ft. (9.2) to illegible
scribe marks in partially healed blaze. (Orig. BT)
NE original BT falls in a skid road.
A 14" (18") fir snag bears N.60°30"E., 65.8 ft. with "36 BT
visible in partially healed double blaze.
A 22" fir bears N.82°E., (N84°E) 38.0 ft. (34.3) with
healed blaze.
A 30" fir bears N.36°W. (N.33°50'W) 33.9 ft. with healed blaze.
Set - Plastic cap in existing 1" iron pipe mkd. "Oregon State Parks"
Set - orange carsonite post with decal mkd. "Property Boundary State
Park Land behind This Sign 2 ft. south.

6/23/88

58

Standard Corner for Sections 2 and 1 only

Found - 1" iron pipe projecting 6" above ground. Ren No. 10
A 30" (15") fir stump bears S.75°E., 21.8 ft. with a badly
decayed face and backcast, no marks visible (Orig.)
A 10" stump bears S.33°W., 13.2 ft. to face with illegible partial
scribe marks (Orig.)
A 16" fir snag bears N.83°20'E., 78.8 ft. mkd. "S 1-BTS 8 BT".
A 16" maple bears S.10°50'W., 57.0 ft. with healed blaze.
Set - Plastic cap in 1" existing iron pipe mkd. "Oregon State Parks".
New BT - An 11" fir bears S.83°E., 21.6 ft. mkd. "T33SR6WS1BT".
Set orange carsonite post with decal mkd. "Property Boundary State
Park Land Behind This Sign" 2 ft. SW.

6/27/88

59

Center 1/4 Corner for Section 2

Set - 5/8" x 30" iron rod with alum. cap 26" in ground. Cap mkd.
"T33S R6W C $\frac{1}{4}$ S2 1988 Oregon State Parks Division".
New BTs - A 13" fir bears N.22°E., 16.29 ft. to 2 finish nails side
and center, mkd. "XBT".
a 14" fir bears N.43°W., 19.55 ft. to 2 finish nails side and
center, mkd. "C 1/4 S2 BT".
Set orange carsonite with decal mkd. "Property Boundary State
Park Land Behind This Sign", 2 ft. NE.

8/17/88

60

1/4 Corner for Sections 1 and 2

Found - Thompson 3/4" iron pipe and BTs but I set a new 1/4 corner
monument as Thompson's I.P. is about 8.5 ft. out of position.
Ren. #16.

Set - 1" x 30" I.P. 26" in ground with 2 3/8" brass cap at single
proportioned position. Cap mkd. "Oregon State Parks T33S R6W
1/4 S2|S1 1988 LS 691".

New measurements to existing BTs:

A 10" madrone bears N.58°E., 21.6 ft. with illegible scribe
marks in partially healed blaze.
A 32" fir bears S.81°W., 24.0 ft. to center with healed blaze.
A 3/4" Iron pipe bears N.41°41'E., 8.56 ft.
Set orange carsonite post with decal mkd. "Property Boundary
State Park Land Behind This Sign" 2 ft. west.

8/16/88

61

Section Corner for Secs. 1, 2, 11 and 12.

Found - 1 1/2" iron pipe 6" above ground from which no evidence of
original BTs.
A 15" black oak bears N.26°E., 18.0 ft. with sawed into healed
blaze.
No evidence of 8" madrone and the BTs mkd. by Reece.
A down 14" fir bears S.30°E., 4.9 ft. no scribing visible.
A 15" black oak bears S.35°W., 51.7 ft. (24.7) with "CS S11 BT"
visible in partially healed blaze.
A 14" fir bears N.20°W., 24.7 ft. with healed blaze.

New Accessories:

8" madrone bears S.58°E., 28.0 ft. mkd. "T33SR6WS12BT".
Set orange carsonite post with decal mkd. "Property Boundary
State park Land Behind This Sign" 2 ft. NW.

6/30/88

John E. Hollingsworth LS #691
For: Oregon State Parks & Recreation
June-Aug. 1988
C.S. 63/62 M 107 - 16

Fd 8/90
M110-48

Fd 8/90
M110-48