

**Douglas County Surveyor's Record of
Government Corners Renewed**

T. 33 T. S. R 6 R. W. W. M.

FOKE-CHAPMAN CO., EUGENE, ORG., 21881

Max Hull
L.S. # 901
For: Gregory Forest
Products
August 1990
112 - 14
S. file 63 / 115

Section corner for 31 & 32 only of T. 32 S. R. 6 W.
Found - 13" dia. madrone N.26½°W., 18.1 ft. blaze healed
12" dia. madrone N. 28½°E., 32.3 ft. blaze healed Ren. # 16A
Set - 5/8" X 30" I.R. w/cap mkd. "Hull RS 901"
New BTs- 10" D. fir S.58°E., 34.0 ft., scribed.
8" D. fir S.23°W., 24.7 ft., scribed.

62

Gerald Nygren
L.S. #1035
For; City of
Glendale
3/94 C.S. 63/134
M 118-79

1/4 Cor. secs. 5 & 8
Set - 5/8" I.R. with yellow plastic cap mkd: "NYGREN LS 1035".
Doug. Fir, 8" dia., bears S.76°W., 24.4', scribed "¼ S8 BT"
Doug. Fir, 8" dia., bears S.67°E., 11.2', scribed "¼ S8 BT"
Doug. Fir, 7" dia., bears N.62°W., 32.2', scribed "¼ S5 BT"
Madrone, 12" dia., bears N.70°E., 28.6', scribed "¼ S5 BT"

63

North ¼ cor. sec. 4
Found two witness monuments -
1" dia. I.P. w/ brass cap wick bears, S.89°26'45"W., 70 ft.
1" dia. I.P. (bent) wick bears, S.00°03'28"E., 76.8 ft.

64

Sec. cor. to 3 & 4 only
Monument FD. -
1" I.R., 20" deep in field NE of Sethers barn
said 1" I.R., bears N.05°12'07"W., 1.45' from computer cor. position.

65

North ¼ cor. sec. 3
Monument set - 5/8" I.R. 30" long 6" below ground
Accessories Fd. - (Brandt cor.) 1" I.R., N.0°0'36"E., 2.25'.
(Brandt ref.) 1" I.R., N.45°33'29"E., 65.45'.
(Brandt ref.) 1" I.R., N.43°55'19"W., 51.18'.
(Brandt ref.) 1½" I.P., N.88°47'58"W., 196.18'.

66

Sec. cor. common to 2 & 3
Monument Set - 5/8" I.R. 30" long 2" above ground
Accessories Fd. - (Brandt cor.) 1" I.R., N.11°55'52"W., 2.62'
(Brandt BT.) 19" Douglas Fir, N.89°W., 38.6', healed
blaze.
(Brandt BT.) 12" madrone, S.5°W., 6.6', visible scribe
New Accessory - 9" Douglas fir, S.58°E., 10.5', scribed "T33S R6W S2 BT"

67

¼ cor. common to 3 & 4
Monument set - concrete nail in pavement using following refs.
Accessories Fd. - (Brandt ref.) 1" I.R., N.33°54'52"W., 34.5'.
(Brandt B.T.) 18" W. oak, N.62°24'E., 29.75', healed blaze
New Accessories - 18" alder, N.3°W., 26.6', scribed "¼ S4 BT".
26" alder, S.59°W., 44.8', not scribed

68

Center one-quarter corner of sec. 3
Monument set - 5/8" I.R. 30" long extended 2" above ground
New Accessories - 14" madrone, N.85°E., 7.4', bark scribed "C¼ S3 BT".
8" madrone, S.36°E., 10.4', bark scribed "C¼ S3 BT".
9" madrone, S.54°W., 7.3' bark scribed "C¼ S3 BT".
5" madrone, N.42°W., 7.7' scribed "X BT"

69

¼ cor. to 3 & 10
Monument set - 5/8" I.R. 30" long extended 2" above ground
New Accessories - 6" Tan Oak, S.10°W., 6.1', scribed "X BT"
5" Madrone, S.84°W., 6.4', scribed "X BT"
5" Tan Oak, N.70°E., 35.9', scribed "X BT"
15" Madrone, N.36°W. 8.2', bark scribed "¼ S10 BT"

70

Gerald Nygren
for: John Sether
11-23-94
M 121 - 31
C.S. 63/134