

Douglas County Surveyor's Record of
Government Corners Renewed

33 S T. S. 7W R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97196

J. W. Cole - Surveyor
E. H. Bahnert - Witn.
Dec. 1, 1923
F.B. 52 Page 4

D. J. Thero
Sept. 6, 1950
C.S. 40/274

Norman D. Price, Registered Professional Land Surveyor.
Work done on survey for Dollar and Patterson Lumber Co, Glendale.
Survey done from March 30, to August 18, 1954.
See County Surveyor's file No. 41/301.

1
COR. 1-36, T 33, 32 S
At corner set 2" iron pipe by proportional measurement, from which
11" Fir N 37° E 1.0 ft.
12" Fir S 69° E 27.8 ft. *NOT COMMON CORNER WHICH?*
FOUND O.K. 12-5-67 J.M.P. → *SI ONLY - FROM RECORD IN FILE, THIS IS PROBABLY NORTH 1/4 COR. SEC. 11*
C.S. 54/36

2
SEC. COR. 2 - 3 - 10 - 11
Found remains of old stake and 3 O.B.T.s which check with Govt.
field notes: The Sugar Pine was entirely gone, and I marked
A Maple 10" dia. S 45° 45' W 25.0 ft.
Set a Creek Boulder 8 x 12 x 15 marked on top + C.S. with 2 notches
on E and 5 notches on South sides.

3
Corner of secs. 3 and 4. (Closing corner). Point for cor. at proportional dist.
There is no remaining evidence of the original closing corner.
Set an iron pipe, 3 ft. long, 2 ins. diam., 28 ins. in the ground,
mkd. RS33;
From which:
A Douglas fir, 30 ins. diam., bears S.47 1/2° E., 98 lks. dist., mkd.
T33S R7W S3 CC RS33 BT.
A chinquapin, 10 ins. diam., bears S.20° W., 114 lks. dist., marked
T33S R7W S4 CC RS33 BT.

4
1/4 sec. corner of sec. 4 only, on N. bdy. of sec. 4, at proportional distance.
Set an iron pipe, 3 ft. long, 1 1/2 ins. diam., 28 ins. in the ground,
mkd. RS33;
From which:
A chinquapin, 7 ins. diam., bears S. 71 1/2° E., 22 lks. dist., mkd.
1/4 S4 RS33 BT.
A chinquapin, 10 ins. diam., bears S.0°30' E., 40 lks. dist., mkd.
1/4 S4 RS33 BT.
FOUND OK. 12/12/67 J.M.P.

5
Corner of secs. 4 and 5, T. 33 S., R. 7 W., (Closing corner.)
Determined by reference to the measurements from the original bearing trees.
Set an iron pipe, 3 ft. long, 2 ins. diam., 28 ins. in the ground,
mkd. RS33;
From which the original bearing trees:
A chinquapin stub, 16 ins. diam., bears S. 83° E., 134 lks. dist.,
on which only axe marks remain. *SEE CORNER NO. #23*
A yellow pine, 20 ins. diam., bears S.47 1/2° W., 142 lks. dist.,
with partial scribe marks visible.
And a new bearing tree:
A sugar pine, 6 ins. diam., bears S.78° E., 25 lks. dist., mkd.
T33S R7W S4 CC RS33 BT.