

Douglas County Surveyor's Record of
Government Corners Renewed

T 33 S. T. S. R. 7. W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 31881

James W. Byron, Deputy County Surveyor
Mike Darby and Wm. Stoffel
January 1963
C. S. File No. 52/140

Marvin C. Ramsey
For J. H. Baxter & Co.
Feb. 4-12, 1965
C. S. File No. 51/310

Section Corner to Sections 11 - 12 - 13 - 14.

Found - All Orig. BT's. Orig. 20"; now 28" R. Fir S.42°W. 10.6 ft., shows scars. Orig. 18", now 26" R. Fir S.72°E. 13.2 ft., shows bark scribing "BT". Orig. 12", now R. Fir N.46°W. 27.7 ft., previously opened, shows scribing.

Orig. 16", now R. Fir N.25°E. 13.9 ft.

Set - Brass Cap at Corner Mkd: County Surveyor's Office, 1963

S11 | S12
S14 | S13

New BT's: Rescribe Orig., now 28" R. Fir S.42°W. 10.9 ft. Mkd: S14 T33S R7WCSBT.

Rescribe Orig., now 26" R. Fir S.73°E. 12.4 ft. Mkd: S13 T33SR7W CS BT.

Rescribe Orig., now 21" R. Fir N.25°E. 15.5 ft. Mkd: S12 T33SR7W CS BT.

12

1/4 Corner to Sections 2 and 11.

Found - 1 1/4" shaft at Cor. & Orig. 15", now 20" Partly rotted Fir Stump that shows good bark scribing.

Also find clump of Laurels that checks for Orig. N.W. BT.

New BT's: 7" R. Fir bears S.34°W. 30.4 ft. scribed 1/4 S11 CS BT.

13" R. Fir bears N.73°E. 11.4 ft. scribed 1/4 S 2 CS BT.

FD. 8/83
D. STEINBERG 5/19/52
11/9/69

13

Sec. Corner to Sections 1 - 2 - 11 - 12.

Determined from the Orig. BT's:

16" D. Fir Snag bears N. 37 1/2° E. 78 lks. dist. with axe face mks. burned out.

36" D. Fir bears S.86°E. 24 lks., with partial scribe mks. on the bark.

Doug. Fir remains of a burned out stump bears S.75°W. 38 lks. dist.

18" D. Fir Snag bears N.78°W. 34 lks. with mkd. T33SR7 on the bark.

Set - I. Pipe 3' long, 2" diam., 28" in the ground, from which:

New BT's: 34" D. Fir bears N.61 1/2°E. 87 lks. mkd. T33S R7W S11 RS404 BT.

28" D. Fir bears S.59°W. 41 lks. mkd. T33S R7W S11 RS404 BT.

26" D. Fir bears N.82°W. 185 lks. mkd. T33S R7W S2 RS404 BT.

14

South 1/16 btwn. Sections 1 and 2.

22.045 Point for the S. 1/16 sec. cor. at proportionate dist.

Set - I. Pipe, 3' long, 1" diam., 28" in ground, mkd. RS404, from which:

22" D. Fir bears S.17°E. 217 lks. dist., mkd. S 1/16 S1 RS404 BT.

12" Madrona bears S.60°W. 72 lks. mkd. S 1/16 S2 RS404 BT.

15

1/4 Sec. Corner to Sections 1 and 2.

Point for the 1/4 cor. at prop. dist., fail to find any evidence of the original corner after careful search.

Set - I. Pipe, 3' long, 1 1/2" diam., 28" in ground, mkd. RS404, from which

10" D. Fir bears S.10 1/2°E. 112 lks. dist. mkd. 1/4 S1 RS404 BT.

8" Madrona bears N.79°W. 34 lks. dist., mkd. 1/4 S2 RS404 BT.

16

66.135 Point for the N. 1/16 Sec. cor. for Secs. 1 and 2. at Prop. Dist.

Set - I. Pipe, 3' long, 1" diam., 28" in the ground, Mkd. RS404 from which:

10" Sugar Pine bears N.34°E. 46 lks. mkd. N 1/16 S1 RS404 BT.

22" D. Fir bears S.84°W. 86 lks. mkd. N 1/16 S2 RS404 BT.

17

Section Corner to Sections 1 and 2 only.

Orig. BT's: 36" Cedar sawed stump bears S.32°E. 20 lks., with axe marks, scribe marks burned out.

32" D. Fir sawed stump bears S.45°W. 28 lks. with ~~22~~ partial scribe mark exposed.

56" D. Fir Snag bears N.60°W., 21 lks. with axe face; marks obliterated from decay.

Set - I. Pipe, 3' long, 2" diam., 28" in the ground mkd. RS404, from which:

An unmarked I. Pipe, 1" diam., 6" above ground, bears S.53°E. 6 lks.

New BT's: 10" D. Fir bears S.57°E. 36 lks. mkd. T33S R7W S1 RS404 BT.

16" D. Fir bears S.10°W. 10 lks. mkd. T33S R7W S2 RS404 BT.

18

RE-RENEWED CORNER NO. 22