

Douglas County Surveyor's Record of  
Government Corners Renewed

T 33 S. T. S. R. 7 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

19

Closing Corner to Sections 2 and 3.

Found - Wooden Stake at Corner.

BLM Tagon Madrona Tree S.83°E. 4.3 ft., old BT.

Stake rotted & just standing, BT., dead & rotten.

Set - Brass Cap at Corner.

New BT's: 16" Chinquapin S.18°48'E. 16.6 ft.

24" Chinquapin S.82°50'E. 28.0 ft.

FOUND O.K. 12/11/67 J.M.P.

Geo. J. Wenderoth  
May, 1965  
C. S. File  
No. 52/140

20

1/4 Corner to Sections 12 and 13.

Found - Orig. 30" Fir, now Stump Hole, S. 2° E. 29 lks.

Orig. 42" Fir, now 48" Short Stump, N. 18° E. 70 lks.

Orig. called distances btwn. the creek agree closely on line.

Set - 1 1/2" Iron Pipe, from which:

BT's: - 20" D. Fir N.48°57'W. 14.80 ft. mkd. 1/4 S RS749 BT.

18" D. Fir N.07°48' W. 46.30 ft. mkd. 1/4 S RS749 BT.

T.A. Mehl III  
For: Rbt. Dollar  
June, 1967  
C.S. File  
No. 55/42

MICROFILM TO HERE 10/67

21

1/4 Corner to Sections 2 and 3.

Found - Orig. 10" Fir bears N.33°W. 38 lks., marked 1/4 S BT.

Tree rotted, ring of bark in place, scribed wood nearby.

Orig. 40" Fir, now a rotten stump, bears S.40°E. 47 lks.,  
marked "1/4 S BT".

Set - 3/4" o.d. galv. Iron Pipe, 36" long, driven 30" into  
ground, cap makred "1/4 S 1543."

12" Madrone bears N. 45° E. 21.6 ft. mkd. "1/4 S2 BT 1543".

10" Chinquapin bears S.44°W. 26.6 ft. mkd. "1/4 S3 BT 1543".

FD. O.K. 3-12-68 J.M.P. C.S. 54/36  
-FD. O.K. 9-23-76 G.L.L. C.S. 55/42

H. W. Lawrence  
For R. Hissong  
Sept 27, 1967  
C. S. File No. 55/9

22

Closing Corner to Sections 1 and 2 only, T33-7W.

Found - 2" I. Pipe with 4" flange at sec. cor., See Ren. #18.

1" I. Pipe S. 53° E. 4.0 ft.

10" D. Fir, now stob, S. 57° E., 23.8 ft., shows pitched  
over scribing.

16" D. Fir, S.10°W. 61.6 ft., shows pitched over scribing.

New BT: 12" D. Fir S. 82° E. 22.3 ft. mkd. T33S R7W S1 CC CS BT.  
12/5/67

John Powell &  
F. Jones  
C. S. File  
No. 54/36

C. C. Sec. Corner to Sections 5 and 4 only, T33-7W.

Found - 2" Iron Pipe at Sec. Cor., See Ren. #5.

Orig. 9", now 18" Y. Pine, S.47 1/2°W. 93.7 ft., tree opened,  
scribe visible.

6" S. Pine, now dead, S.78°E. 16.3 ft., scribe visible.

New BT: Chinquapin S.30°E. 17.3 ft. mkd. T33S R7W S4 CC CS BT.

Note - This corner lies on top of ridge running NE-SW about 60 ft.  
south of old road intersection. 12/12/67

(Not Renewed) 23

RE-RENEWED CORNER

24

Standard Corner of Sections 35 and 36 only, T32-7W.

Found - Orig. 30" Fir Stump N.35°E. 10.0 ft., old hack marks  
outline face.

Orig. 16" Fir Stump N.47 1/2°W. 24.0 ft., only root collar  
remains.

Orig. 28" Fir Stump S. 7°E. 13.0 ft., bark scribing reads "BT".

Set - 1 1/2" ID Iron Pipe for the corner & scribed following BT's:

16" Doug. Fir N. 33° W. 17.5 ft.

12" Doug. Fir N. 27° W. 15.0 ft.

17" Live Oak S0°30' E. 32.0 ft.

All bearings were taken with a staff compass; Var. 19°00'E.  
Distances were measured with a steel tape. This corner was  
renewed in 1954; Information was verified by T. H. Mehl III,  
RS 749, Dec. 21, 1967.

Milner L. Larson  
Robert Dollardo.  
Dec. 21, 1967  
C. S. File No 55/15