

Douglas County Surveyor's Record of
Government Corners Renewed

T. 33 S. T. S. R. 7 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

31

Section Corner to Sections 9 - 10 - 15 - 16.
Found - Orig. 12", now 17" Laurel, N. 50° E. 9.9 ft., opened for scribe, "BT".
Orig. 46", now 52" D. Fir, S. 10° W. 18.5 ft., no marks visible.
No trace of S.E. or N.W. BT's.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1968
Doug. Co. T33S R7W
S 9 | S 10
S 16 | S 15
Jos. Co.
New BT's: 14" D. Fir N. 78½° W. 16.2 ft. mkd. T33S R7W S9 CS BT.
15" D. Fir N. 53° E. 17.6 ft. mkd. T33S R7W S10 CS BT.
7" B. Oak S. 8½° E. 28.7 ft. mkd. T33S R7W S15 CS BT.
Reblzd. & Resrbd: 52" D. Fir S. 10° W. 18.5 ft. mkd. T33S R7W S16 CS BT.
4/3/68

32

Section Corner to Sections 31 and 32 only, T32-7W.
Found - 16", now 26" D. Fir, N. 1½° E. 55.4 ft., open & show scribing.
18", now 28" D. Fir, N. 72° W. 72.6 ft., open & shows scribing,
and bark scribed "BT".
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1968
T32S R7W S 31 | S 32
T33S S 6
New BT's: 6" D. Fir N. 17° E. 17.0 ft., scribed T32S R7W S32 SC CS BT.
8" D. Fir N. 64° W. 11.4 ft., scribed T32S R7W S31 SC CS BT.
Note - This corner lies 660' E. of top of ridge, running N & S. and
603.9 ft. west of Closing Corner to Sections 6 and 5., see below.
5/27/68

Cl. C. Section Corner to Sections 6 and 5 only, T33-7W. 33

Found - 1" I. Pine 24" long at corner. (No trace of corner stone)
15" D. Fir, now 24" Snag, S. 57° W. 66.0 ft., shows bark scribing.
32" Sugar Pine, now 42", S. 81° E. 51.5 ft., shows a scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1968
T32S T33S R7W CC S 32
S 6 | S 5
Rescribed: 42" S. Pine S. 81° E. 51.5 ft. scribed T33S R7W S5 CC CS BT.
New BT: 10" D. Fir N. 69° W. 71.0 ft. mkd. T32S R7W S32 CS BT.
Note - There were no other trees for scribing.
This corner lies 603.9 ft. East of S.C. of S31/S32, see above.
5/27/68

34

¼ Corner to Section 3 and 10.
Found - 44" D. Fir, now 50" Snag Top, S. 3° W. 8.6 ft., bark scribe visible.
48", now 52" S. Pine, North 31.7 ft., no marks visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1968
T 33 S R 7 W
¼ S 3
S 10
Reblzd. & Resrbd: 52" S. Pine N. 31.7 ft. mkd. ¼ S3 CS BT.
New BT: 7" Tan Oak S. 46° E. 29.1 ft. mkd. ¼ S10 CS BT.

35

Section Corner to Sections 4 - 5 - 8 - 9.
Found - 1½" I. Pipe & Old BT's., plus 2 other BT's., approx. 15 years
old which are unrecorded:
22" S. Pine N. 66° W. 31.7 ft., shows scribing.
22" D. Fir, S. 53° E. 26.0 ft., opened & found scribing.
Orig. 5" Chinquapin, now 10", N. 53° E. 12.5 ft., shows scribing.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1968
T 33 S R 7 W
S 5 | S 4
S 8 | S 9
Rescribed: 10" Chinquapin N. 53° E. 12.5 ft. mkd: T33S R7W S4 CS BT.
22" D. Fir S. 53° E. 26.0 ft. mkd. T33S R7W S9 CS BT.
New BT's: 10" Chinquapin N. 67° W. 21.8 ft. mkd. T33S R7W S5 CS BT.
10" Laurel S. 39° W. 25.3 ft. mkd: T33S R7W S8 CS BT.
Note - This corner lies on top of small spur.
6/4/68

36

¼ Corner to Sections 6 and 5.
Found - No trace of Corner Stone.
10", now 12" Laurel, S. 43° E. 22.4 ft., open & shows scribing.
12", now 18" D. Fir, N. 30° W. 4.6 ft., shows bark scribing.

(continued next page)

John M. Powell
Frank Jones & W. Penley
May and June, 1968
C. S. File No. 54/36