

Douglas County Surveyor's Record of
Government Corners Renewed

T. 33 S. T. S. R. 7 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97401

(continued)

Set - Brass Cap at Cor.Mkd: County Surveyor's T 33 S R 7 W
Office, 1968 $\frac{1}{4}$ S 6 | S 5

Rescribed: 18" D.Fir N.30°W/ 4.6 ft., scribed $\frac{1}{4}$ S 6 CS BT.

Note - This $\frac{1}{4}$ corner lies north-south cutting line & 360' S. of a creek.

37

$\frac{1}{4}$ Corner to Sections 5 and 8.

Found - No trace of Corner Stone.

20" D.Fir, now Snag, S.4°E. 12.5 ft., opened for scribe, "8".

18" D.Fir, now stump, N.43°E. 23.1 ft.

Set - Brass Cap at Cor.Mkd: County Surveyor's T 33 S R 7 W
Office 1968 $\frac{1}{4}$ $\frac{S 5}{S 8}$

New BT's: 11" D.Fir S. 46° E. 47.3 ft., mkd: $\frac{1}{4}$ S8 CS BT.

12" D.Fir N. 4° E. 152.5 ft. mkd: $\frac{1}{4}$ S5 CS BT.

38

$\frac{1}{4}$ Corner to Sections 8 and 9.

Found - 14" D.Fir Corner Tree, now 16", good scars on E-W Faces.

18" D.Fir, now snag, East 2.0 ft., opened for scribing "S".

14" D.Fir, now 12' high stob, S.48°W. 14.5 ft.

Set - Brass Cap on W. side of 17" Corner Tree, mkd:

County Surveyor's T 33 S R 7 W Doug. Co.
Office 1968 $\frac{1}{4}$ S 8 | S 9 Jos. Co.

New BT's: 26" D.Fir S.35°W. 20.0 ft. mkd. $\frac{1}{4}$ S8 CS BT.

39" D.Fir N.20°E. 25.1 ft. mkd. $\frac{1}{4}$ S9 CS BT.

39

$\frac{1}{4}$ Corner Section 6 only, T33-7W.

Found - Corner Stone 12x10x5 mkd. " $\frac{1}{4}$ ".

20", D.Fir, now 28" Snag, N.25°E. 21.8 ft., opened & found scribing.

Set - Brass Cap at Cor.Mkd: County Surveyor's T 33 S R 7 W
Office 1968 $\frac{1}{4}$ S 6 Doug. Co.

Jos. Co.

New BT's: 40" D.Fir N.85°E. 95.3 ft. mkd: $\frac{1}{4}$ S6 CS BT.

26" D.Fir Snag N.32 $\frac{1}{2}$ °E. 16.3 ft. mkd. " $\frac{1}{4}$ S6 CS BT.

Note - There are no other living trees in range for scribing and this corner lies 264 ft. south of top of ridge.

40

$\frac{1}{4}$ Corner to Section 1 only, T33-8W.

Found - No trace of Corner Stone or SW BT. due to logging.

10" D.Fir, now 26" Snag, N.18°W. 29.7 ft., opened & found scribing.

Set - Brass Cap at Cor.Mkd: County Surveyor's T 33 S Doug. Co.
Office, 1968 RSW $\frac{1}{4}$ S 1

New BT's: 22" D.Fir S.82°W. 50.9 ft. mkd: " $\frac{1}{4}$ S1 CS BT.

40" Y.Pine S.35°W. 52.0 ft. mkd: " $\frac{1}{4}$ S1 CS BT.

41

Center of Section 2, Center $\frac{1}{4}$ Corner.

Set - 5/8" Iron Rod, from which

Scribed - 6" Madrone N. 36° W. 2.90 feet.

4" Madrone N. 67° E. 34.84 feet.

4" Madrone S. 42° 45' E. 73.25 feet

Power Pole S. 26° 15' W. 77.92 feet.

Mar. 29, 1971

North 1/4 Corner Section 2, T33-7W.

Set - 5/8" Iron Rod and Scribed:

10" Madrone S. 55° W. 26.90 ft.

8" Madrone S. 11° E. 16.10 ft.

Found - 1" I.P. N. 9°33'W. 17.28 feet.

NOTE: MAY
NOT BE PROPER
1/4 COR.
V.R. 7/62
SEE BLM
VOL. 91 P6
16267
3/29/71

John M. Powell
Frank Jones & W. Penley
May and June, 1968
C. S. File No. 54/36

MARCH 71

Masters,
Claude E.
For: Corwin
C.S. File
55/192
M 41 - 39

C.E. Masters
For: Corwin
M 41 - 39

JAN. 1972

3/77