

Douglas County Surveyor's Record of
Government Corners Renewed

T 33 T. S. R 7 R. W. W. M.

KOKE-CHARMAN CO., EUGENE, ORE. 21881

43

1/4 Corner for Secs. 11 and 14.
Set - 1 1/2" Iron Pipe per survey by Richard Templin, Jr. filed with
the Josephine County Surveyors Office as CS 148-77.
BT's- A S. Pine, 45" bears N.15°W., (Rec. N.10°W.) 64.02 ft. OBT.
A D. Fir, 15" bears N.60°E., 3.0 ft.

Richard L. Templin, Jr.
For: C & D Lbr. Co.
July 11, 1977
C.S. 58/93

7/11/77

44

Section corner common to Secs. 31 of T32-6 and 36 of T.32-7 only
(On North boundary of Sec. 1, T.33-7)

Set - 1" x 30" Iron rod, flush.

From which:

3" dwarf apple bears S.66°30'E., 4.41 ft.

4" peach, bears S.82°W., 14.50 ft. Trees measured to trunk centers
not marked.

Fenceline 25 ft. north. An 1855 closing- corner re-set using single
proportion measure.

Ronald Brandt
For: Ronald and
Linda Brandt
July 1979
M 78 - 48

7/79

45

Center 1/4 Corner for Section 10

Set - Oregon State Dept. of Forestry 1 1/2" x 36" alum. pipe with 3 3/4"
alum. cap and magnetic insert, 30" in the ground.

BT's - 4" fir bears S.15°E., 7.5 ft. with bearing tree tag.

4" fir bears S.71°W., 9.6 ft. with bearing tree tag.

Lloyd D. Smith
State of Oregon
Dept. of Forestry
March 5, 1985
M 98 - 47

3/5/85

46

1/4 Corner for Sections 8 and 9

Found - 2 1/2" dia. 1968 DCSO brass cap on a 1 1/2" O.D. I. Pipe protruding
8" above ground. Ren. No. 38

14" now 16" dia. 2 ft. high stump, no marks visible (Orig. Cor. Tree)

DCSO BC/IP bears West 1.0 ft. from corner tree (agrees w/1975 BLM
Dependent Resurvey)

18" now 14" d. Fir snag with scribe mark visible "S" has a healed
lower blaze, bears East 3.3 ft. (agrees w/1975 BLM rec.) Orig. BT)

14" now 15" dia. D. Fir snag with a healed blaze bears S.51°W., 15.8 ft.
(Rec. S.48°W., 15.8 ft.) Orig. BT.

26" now 24" dia. D. Fir with a partially healed single blaze
scribing visible "1/4 S8 CS BT" bears S.35°W., 19.5 ft. (Rec.
S.35°W., 19.8 ft.) Ren. No. 38

39" now 42" dia., D. Fir with a fully healed single blaze bears
N.20°E., 24.4 ft. (agrees w/1975 BLM rec.) Ren. No. 38

1975 BLM bT, s.40°W., 39.6 ft. is gone.

New BTs - 4" Madrone bark scribed "1/4 S8 CS BT" bears S.56°W., 19.2 ft.

19" D. Fir single blazed "1/4 S9 CS BT" bears N.45°E., 50.5 ft.

Corner lies in a steep slide area approx. 50 ft. West of road.

Douglas County
Surveyors Office
Randall Smith,
Deputy -
Stephen Flause
Oct. 20, 1992
C.S. File 64/32

10/20/92