

west on line between sec 8-17

36.50 summit of Hill

40.00 get post from which

a Laurel 14" dia N.7W 100 lbs

Red Fin 28" " S 85° E 45 lb

~~79.04~~ to sec cor corner to 8-9-17-18

North between 16 & 17

400 road SW.

~~15~~ set post

40.00 set post

W. O. 30 in dia S 20 W 130 lbs

" " 17 " " N 60 E 150 lb

56.50 Enter post

~~set~~ 80.00 set post on sec 8-9-16-17
corner of road.

North on line between 17-18

40.00 set post same road

80.00 set sec post 7-8-17-18

524
2095
1326
1126
416
C.S. File No. 416

Between Secs. 17 - 18

Twp. 27 S. R. 4 W.

On random between Secs.

Intersect _____ Lks. _____ of Corner _____

On true line between Secs.

Ch 4000

Set Quarter Post found, from which a

Dia. Bears.

Dia. Bears.

8000

To Corner 7-8 - 17-18

W Oak 20m dia N47W 306 lks

" " " " " N69E 192 "

B " " " " N83E 400 "

Location Sec 17-727-4

Sheet No. 1

TRAVERSE SURVEY AND CALCULATION OF AREA

M. B. GERMOND, County Surveyor

Computed by W. H. Apple

Checked by

Date Apr 2 1920

Owner Mathews

Station	COURSES		LATITUDE		DEPARTURE		LATITUDE		DEPARTURE		M. D.	D. M. D.	N AREA	S AREA	D. Sin.	L. Cos.
	Bearings	Distance	North	South	East	West	North	South	East	West						
1	E	15.32		0	15.32	0	0	0	0	0	15.32	15.32		0.84	1	0
2	S	60		60.0		0	60.24		0		30.64	30.64	1844.96	1844.96	0	1
3	N	2.5		0		2.5	0.01		2.5		28.14	28.14	0.28	0.28	0	0
4	N16°42'W	20.8	19.92		5.98		5.98		5.98		19.66	19.66	390.13		1	0
5	N9°22'W	46.25	40.68		6.84		6.84		6.84		6.84	6.84	277.25		1	0
		159.87	60.50		15.32		60.379		60.279				667.38	1846.08	28736	95782
			0.0357										667.38	667.38	16591	84614
													1178.70	1178.70		
													2178.70	2178.70		
													5893	5893		

