

C. S. No. 4-37

1 Survey for G.W. Finley Sec 23-T27-7
 Sta Def L R M C C
 Dec 29-1922

Began at Corner to Secs 23-24-25-26
 witness. One SW corner but
 set iron pin $\frac{1}{4}$ " x 38" also marked.

Sec Cor Thane 1894 Var $21^{\circ}45'$

Nest
 303
 $+ 7^{\circ}30'$
 200°
 $+ 8^{\circ}15'$
 200°
 $+ 9^{\circ}15'$
 159°
 $+ 7^{\circ}45'$
 151°

$\Delta 1$ $0^{\circ}15'R$

228
 $+ 5^{\circ}45'$
 200°
 290°
 151°

$\Delta 2$ $0^{\circ}15'L$

157
 $+ 8^{\circ}30'$
 138°

$\Delta 3$ $0^{\circ}19'$

$N 89^{\circ}40' W$ $N 89^{\circ}41' W$

$\Delta 4$ $1^{\circ}20'L$

$589^{\circ}90' W$ $589^{\circ}59' W$

$1^{\circ}35'$
 $0^{\circ}34'$

which I renewed from 3 original
hole, where tree stood stable
oak stake 4x4x40 properly

303
1199 1/2
1480
1480
1503

1492
1490

N 0.9

1492
1490
1503

N 0.9

Sta	Def L	Def R	M/C	C.C.	Dist.
			589°10'W		113° - 5°20' 90° 33
Δ 5	1°01'	1°01'R	West		+ 8000' 1668
Δ 6	0°38'L		589°20'W 589°22'W		+ 14000' 200° + 9000' 833
Δ 7	0°00'		589°29'W 589°27'W		+ 14015' 200° + 14020' 602
Δ 8		0°57'R	N 89°30'W N 89°41'W		+ 14000' 1661
Δ 9	0°00'				+ 14000' 1108
Δ 10	0°00'				- 20015' 78°
Δ 11	0°19'L			West	- 25030' 115°
Δ 12	Approx 1/4 Col				
	0°57'	1°58'			

1130
896
330

547

1657
1940
823

530

1938
584

528

1611

N10

(2358)

N006

N0E

Approx. 1/2 car load. 23/26 727-744

Det Oak post E. Mound of Rock from white

W Oak 10" dia

N 53° 15'

264

W " 30" dia

S 37° 30' E

44

17
17
17

3

CS 1/37

CS FILE FOLDER

CONTAINS

MORE

INFORMATION