

DEPARTMENT OF THE INTERIOR
OFFICE OF U. S. SURVEYOR GENERAL

Portland, Oregon, April 21, 1914.

Mr. William Seyler,
Olalla, Oregon.

Sir:

In reply to your letter of the 20th inst., I will state that the following is a true and correct copy of the field notes on record in this office of the line between secs. 8 and 17, T. 29 S., R. 7 W., W.M., Oregon:

From the cor. of secs. 7, 8, 17 and 18, which is a post; from which
 ✓ A B. oak, 14 ins. diam., bears S.72°E., 59 lks. dist.
 ✓ A B. oak, 9 ins. diam., bears N.43½°E., 72 lks. dist.
 ✓ A B. oak, 24 ins. diam., bears N.42°W., 8 lks. dist.
 ✓ A B. oak, 8 ins. diam., bears S.66°W., 68 lks. dist.
 I run East on a random line bet. secs. 8 and 17.
 Va. 18°30'E.

40.00
80.70
10.50
32.00
35.00
40.35

Set temp. ¼ sec. post.
 Intersect E. boundary, 50 lks. N. of sec. cor.
 N.89°38'W. on true line bet. secs. 8 and 17.
 Top of ridge.
 Foot of hill; enter bottom.
 Ten Mile Creek, 18 lks. wide, course North.
 Set ¼ sec. post at average dist.; from which
 A B. oak, 9 ins. diam., bears N.78°W., 21 lks. dist.
 A B. oak, 12 ins. diam., bears S.10°W., 27 lks. dist.
 To sec. cor.
 2nd rate soil.
 Timber, oak & fir
 Underbrush, oak and hazel.

 North bet. secs. 16 and 17.

Set post cor. to secs. 8, 9, 16 and 17; from which
 A. W. oak, 18 ins. diam., bears S.34°E., 247 lks. dist.
 A B. oak, 18 ins. diam., bears N.20°E., 105 lks. dist.
 A B. oak, 16 ins. diam., bears N.14°W., 117 lks. dist.
 A B. oak, 12 ins. diam., bears S.50°W., 128 lks. dist.

80.00

10
16
630
630
67.30
117
66
702
702
77
120
705
84.40

C. S. File No. 22/9

Between Secs. 18-19

Twp. 29 S. R. 7 W.

S 89° 45' E

On random between Secs.

Intersect

Lks.

of Corner

On true line between Secs.

18-19

42.69 ✓

Set Quarter Post

from which a

Laurel 6"

Dia. Bears. S 20° W 11 lks ✓

" 6"

Dia. Bears. N 58° E 15 lks ✓

53.00

Sheave

72.30

Red Fir 24"

82.69 ✓

To Corner

Between Secs. 17-20

Twp. 29 S. R. 7 W.

On random between Secs. 17-20

Intersect _____ Lks. _____ of Corner

N 89° 30' W

5.00
10.00

On true line between Secs. 17-20

Foot of steep bluff
Top of bluff

40.22 ✓

Set Quarter Post

from which a ✓

W. Oak 24"

Dia. Bears. N 5° W 18 lks

B " 18"

Dia. Bears. S 74° W 38 ✓

55.00

Shears

80.44 ✓

To Corner

Between Secs. 8-9

Twp. 29 S. R. 7 W.

North	Between Section <u>8</u> and Section <u>9</u>
10.25	Pine 30"
30.00	Top of Ridge
40.00	
	Set Quarter Post " ✓ from which a ✓
	Lance 14 N 24° E Dia. Bears. 25 lbs ✓
	" 18" Dia. Bears. N 80° W 30 lbs ✓
55.50	Ten Mile Ck
80.00	Set Post Corner to Sections 4-5-8-9 from which a ✓ ✓
	B Oak 24 Dia. Bears. N 40° E 600 ✓
	B Oak 28 Dia. Bears. N 33° W 630 ✓
	Dia. Bears.
	Dia. Bears.

Between. Secs. 20-29

Twp. 29 S. R. 7 W.

On random between Secs.

Intersect

Lks.

of Corner

$N 89^{\circ} 43' W$

On true line between Secs. 20-29

15.00
23.00

Ten Mile Creek
Foot of hill

40.38

Set Quarter Post

from which a

B Oak 9
Pine 8

Dia. Bears. $56^{\circ} E$ 27 \checkmark
Dia. Bears. $N 10^{\circ} E$ 36 \checkmark

50.00

Top of ridge

80.76

To Corner

A. E. McCulloughs 2-0 Not 154

@ no 46 in 29-7

159.50 acres

Begin at pt 6.00 chs S and 10.00 chs
E of SE cor of Sec 20. Post

W. Oak 8" S70°W 10 lks ✓

W " 14" S30°W 17 lks ✓

North

6.00 Int line bet 21-28 10.00 chs

E of SE cor of Sec 20

30.00 Foot of hill

65.00 Post

Fir 30 S34 lks ✓

Ash 6" ^{only} East 10 lks

West

10.00 Olalla ck

10.00 Post

Fir 10" S40°W 16 lks ✓

Larch 8" S50°W 38 lks ✓

South on line bet Secs 20-21

19.00 1/4 post bet Secs 20-21 away

2.00 chs N of McCulloughs house

20.00 Post

3u 30" S 20° E 40 links ✓

200 10" S 60° W 44 ✓

West

Post

21.00

Pine 14 N 45° W 312 ✓

Ash 14 S 10° W 434 ✓

South

Dia. Bears.

Dia. Bears.

Dia. Bears.

Dia. Bears.

05.11

Ollala crk

05.25

Rocky approx

Set Post Corner of Section from which a

45.00

Post

W Oak 5" N 45° E 42 ✓

stump

East

12.50

Ollala crk

Dia. Bears.

20.91

Post Pine bet 28-29

6.00 eas

Dia. Bears.

Top of stump bet 20

30.91

To begin

Between Section

8-9

and Section

9

Between Secs.

8-9

Twp.

29

S. R.

7

W.

no left.

John Byron Hill Not. 157

Q 38 m 29-7 160.19 ac

Beg at NW corner 38. Post

W. Oak 8" N20°W 154 lks ✓

South var 190°E

57.00 Post

Yel Pine 18" N60°E 393 lks ✓

W. Oak 18" N49°E 486 ✓

East

4.00 cks

15.50 Post

B Oak 12" N60°E 124 lks ✓

W Oak 18" N40°E 134 ✓

North

17.50 Post, no lines

East

4.35 ✓ Int line bet posts 28-29

8.4½ chs S of 1/4 Post

18.00 Post

W. Oak 18" N89°W 480 lks

North

39.50 Post

B Oak 20" N70°W 23 lks ✓

B " 12" N50°W 31 lks ✓

West

33.76 to beg

Between Secs. 29-32
 Twp. 29 S. R. 7 W.

On random between Secs.

Intersect Lks. of Corner

N89°30' W

On true line between Secs. 29-32

10.75

33.00

Ten mile Cr.
Foot of hill

40.32

Set Quarter Post from which a

W. Oak 14

Dia. Bears. N45°E 225° ✓

" " 12

Dia. Bears. S30°E 150° ✓

44.00

Top of hill

80.64

To Corner

Between Secs. 29-30
 Twp. 29 S. R. 7 W.

North
 2.50

Between Section 29 and Section 30
 Sugar Pine 60"

40.00

Set Quarter Post from which a
 Pine 36 Dia. Bears. S 61° W 69 ✓
 B. Oak 14 Dia. Bears. N 87 ¹/₂ ° E 109 ✓

80.00

Set Post Corner to Sections 19-20-29-30 from which a
 Laurel 4 Dia. Bears. N 72° E 12 ✓
 // 4 Dia. Bears. S 48 E 14 ✓
 // 8 Dia. Bears. N 86 W 24 ✓
 // 4 Dia. Bears. S 83 W 25 ✓

Between Secs. 19 - 20

Twp. 29 S. R. 7 W.

North

Between Section 19 and Section 20

25.00

Stream

40.00

Set Quarter Post

from which a

In 8" S77° E

Dia. Bears.

11 lks ✓

" 10" S64° W

Dia. Bears.

6 lks ✓

60.00

Top of ridge

80.00

Set Post Corner to Sections

from which a

Red In 18

Dia. Bears. S42½° E

~~12~~ 12 ✓

" " 8

Dia. Bears. N51° E

12 ✓

" " 14

Dia. Bears. N47° W

11 ✓

" " 15

Dia. Bears. S16° W

14 ✓

Between Secs. 28-29

Twp. 29 S. R. 7 W.

North

Between Section 28 and Section 29

40.00

Set Quarter Post

from which a

Pine 36 ✓
made md

✓ ✓
Dia. Bears. S27°E 525

Dia. Bears.

80.00

Set Post Corner to Sections

from which a

B Oak 9

Dia. Bears. S20°E 81 ✓

" " 16

Dia. Bears. N21°E 19 ✓

W " 18

Dia. Bears. N24°W 80 ✓

B " 8

Dia. Bears. S64°W 62 ✓

Between Secs. 20-21
 Twp. 29 S. R. 7 W.

North Between Section 20 and Section 21

30.00 Ten Mile Ck

40.00 Set Quarter Post from which a
 Laurel 8 Dia. Bears. $S10^{\circ}E$ 85 ✓
 Red In 10 Dia. Bears. $N20^{\circ}E$ 68 ✓

80.00 Set Post Corner to Sections 16-17-20-21 from which a
 Laurel 8 Dia. Bears. $S10^{\circ}E$ 85 ✓
 Red In 10 Dia. Bears. $N20^{\circ}E$ 28 ✓
 Laurel 4 Dia. Bears. $N53^{\circ}W$ 23 ✓
 11 8 Dia. Bears. $S8^{\circ}W$ 50 ✓

Look out Copied wire scratched out fig 68

Between Secs. 8-17

Twp. 29 S. R. 7 W.

On random between Secs.

Intersect Lks. of Corner


N 89° 38' W

10.50

32.00

35.00

40.35



On true line between Secs. 8-17

Top of ridge
Foot of hill
Two mile Ok

Set Quarter Post

from which a

B Oak 9

Dia. Bears. N 78° W ^{13.9} 21 lks ✓

" " 12

Dia. Bears. S 10° W 27 ✓
17.8

80.70 ✓

To Corner

66
126
192

21
66
126
192
258

27
66
132
198
265

Sta x

Grade Ground x

0.01714 per ft.

0+00

+20

+40

+60

+80

1+00

+20

+40

+60

1+80

445.40

449.72

4.32 ✓

4'

37/8 ✓

445.08

48.93

3.85 ✓

3'

10 1/4 ✓

444.73

48.91

4.18 ✓

4'

2 1/8 ✓

444.39

48.73

4.34 ✓

4'

4 ✓

444.05

48.79

4.74 ✓

4'

8 7/8 ✓

443.69

48.18

4.49 ✓

4'

5 7/8 ✓

443.34

48.41

5.07 ✓

5'

0 7/8 ✓

443.00

42.53

Between Secs. 17-18

Twp. 29 S. R. 7 W.

North

10.30

17.00

30.00

Between Section 17 and Section 18

Red Fir 10"

Began to sound sleep hill

Shenan

40.00

Set Quarter Post

from which a

B Oak 8"

Dia. Bears. 540°W 57 lks ✓

W Oak 40"

Dia. Bears. N79E 82 lks ✓

80.00

Set Post Corner to Sections 16-17²⁰⁻²¹ from which a

B Oak 14 dent

Dia. Bears. 572°E⁵⁷ 79 lks ✓

" " 9 dent

Dia. Bears. N43½°E 72 ✓

" " 24 pine

Dia. Bears. N42°W 5? 8 ✓

" " 8 dent

Dia. Bears. 366°W 68 ✓
449

72
66
432
432
4752

66
8
528
72
66
432
432
4752
79
66
474
474
5214
68
66
408
408
4488
66
79
594
462
5214

File under Traylor

Page 1 of 1

Traverse Notes for Traverse line 1/4 Cor to Sec Cor.

$\frac{8}{17} - - - \frac{8+9}{17+16}$

L. G. HICKS
CIVIL ENGINEER
ROSEBURG, OREGON

Calculated by Hicks
Checked by L. G. Hicks
Date May 2 1917

STATION	DISTANCE	BEARING	EAST	TOTAL EAST	WEST	TOTAL WEST	NORTH	TOTAL NTH	SOUTH	TOTAL STH	D. M. D.	NORTH	SOUTH
1/4 Cor 817	904.4	East	904.4	904.4									
	269.5	S87°21'E	269.2	1173.6					12.5	12.5			
	315.6	N89°58'E	315.6	1489.2			0.2		12.3	24.8			
	269.4	S85°41'E	269.2	1758.4					32.2	57.0			
	77.8	S85°34'E	77.6	1836.0					38.2	95.2			
	181.0	N86°15'E	180.6	2016.6			11.8		26.4	121.6			
	185.7	N87°29'E	185.5	3202.1			8.2		18.2	139.8			
	326.1	N90°57'E	56.3	3258.4			321.2	303.0		141.0			
to Sec Cor.													
							341.4		38.4				
							38.4						
							303.0						

Handwritten notes:
N 82° 21' E
N 82° 21' E
N 82° 21' E
N 82° 21' E

8219

(10)

North bet Secs 8 & 9

10.25 Pine 30"

30.00 Top of ridge

40.00 set 1/4 post

Laurel 14" N24°E - 25 lbs

" 18" N80°W - 30 "

55.50 One Mile Cr N75°E

64.00 Enter prairie

67.50 Field

78.50 leave field

80.00 set post Cor Secs 4, 5, 8 & 9

Black 24" N40°E - 400 lbs

" " 28" N33°W - 630 "

Made mound

S. File No. 22/9

(2)

North bet Secs 14 + 15

40.00 Set 1/4 Cor

B. Oak 24" S 30° W - 75

" " 30" N 20° E - 50

80.00 Set post Cor Secs 10, 11, 14 + 15

Lawrel 18" S 18° W - 50 lbs

" 6" S 30° E - 53 "

" 4" N 58° W - 17 "

" 5" N 40° E - 15 "

North bet Secs 10 + 11

40.00 Set 1/4 post

a W Oak 20" S 50° W - 100

B " 4" S 30° E - 50

80.00 Set post Cor. Secs 2, 3, 10 + 11

W. Oak 24" S 25° W - 105

B " 18" S 10° E - 225

W " 20" N 15° E - 62

" " 36" N 45° W - 50

S. File No. 22/9

(1)

Cor Secs. 22, 23, 26 & 27

Red Fir 18" S13°E - 20 lks

Cedar 24" S50°W - 21 "

Red Fir 20" N45°E - 14 "

" " 12" N43°W - 7 "

North bet 22 & 23 Van 18 1/2°E

10.00 Stream 10 lks S10°W

33.20 Cedar 50"

40.00 Set 1/4 post

Laurel 4" N5°W - 22

" 4" N53°E - 20

57.00 Sharp ridge

80.00 Set post Cor Secs

14, 15, 22 & 23

Laurel 15" S35°E - 17

" 4" S86°W - 70

" 6" N55°W - 50

" 18" N80°E - 28

C. S. File No. 22/9

(3)

North bet Secs 27 & 28

40.00 Set 1/4 post

Red Fir 8" S 39° E - 15 lks

Logwood 6" N 40° W - 7 "

80.00 Set post Cor Secs 27, 22, 27 & 28

Laurel 18" S 35 1/2° E - 153

B. Oak 20" N 38 1/2° E - 50

Laurel 8" N 32° W - 97

B. Oak 8" S 52° W - 166

N 89° 45' W on true line bet 22 & 27

40.12 Set 1/4 post

Red Fir 10" S 45° W - 28

" " 8" N 25° W - 10

80.24 See Cor.

S. File No. 22/5

(6)

North bet Secs 9 & 10

40.00 Set $\frac{1}{4}$ post

Red Fir 9" N42°E - 27

Alowood 4" S77°W - 10

48.00 Enter bottom

60.50 Begins ascend hill

80.00 Set Sec post

3, 4, 9 & 10

B. Oak 10" S52°E - 55

Laurel 16" N65°E - 38

Red Fir 30" N53°W - 24

" " 24" S26°W - 18

C. & E. No. 22/9

CS FILE FOLDER

CONTAINS

MORE

INFORMATION