

Bench Mark - Bridge Spike in R.R.
Signal Line Pole
Assumed Elevation 500 ft.

	C.	B.	A.
0+00	499.92	499.84	499.7
0+20	499.94	499.82 +	499.80
0+40	499.63	499.58 +	499.69
0+60	499.74	499.82 +	500.02
0+80	499.92	500.00 +	499.98
1+00	500.07	499.91 +	499.96
1+20	499.60	499.56 +	499.40
1+40	499.50	499.29 +	499.34
1+60	499.46	499.25 +	499.29
1+80	499.49	499.32 +	499.38
2+00	499.60	499.25 +	499.40
2+20	499.41	499.30 +	499.26
2+40	499.02	498.82 +	498.92
2+60	498.70	498.47 +	498.58
2+80	497.96	497.89 +	498.08
3+00	496.80	496.81 +	497.14
3+20	495.72	495.49 +	495.77
3+40	495.76	495.62 +	495.48
3+60	496.29	496.01 +	495.83

360.0 ft



**COUNTY SURVEYOR'S OFFICE
DOUGLAS COUNTY OREGON
ELEVATIONS FOR MILLSITE
SECTION 28, T28S, R6W. W.M.**

BEN B IRVING COUNTY SURVEYOR
SURVEYED MARCH 27 1947 BY
NE RICHARDSON DEPUTY
SCALE 1" = 20'

COUNTY SURVEYORS FILE DATA
DO NOT REMOVE FROM OFFICE