

Subdivision of Section 27
T. 31 S., R. 4 W.

for
Clair Lumber Co.
Glendale, Oregon.

Geo. J. Wenderoth.

Surveyor.

December 1947.

REGISTERED
OREGON
LAND SURVEYOR

Geo. J. Wenderoth

MARCH 10, 1944
George J. Wenderoth
5

North Line Section 27. #1

Begin Corner 27-28-21-22

Found 20" Fir S. $14^{\circ}30'W$. 20.5 ft.

Drive $1\frac{1}{4}$ " Iron pipe for Corner.

Mark 8" Yew S. $65^{\circ}18'E$. 45.9

4" Hemlock N. $5^{\circ}30'E$. 53.5

26" Fir N. $33^{\circ}W$. 60.1

Run East Var. 21°

340.0 Top ridge

1300.0 Creek Course S.W.

2340.0 Top Spur.

2376.0 Logging Rd.

2630.1 $\frac{1}{4}$ Cor. bet. 22 + 27

Find both trees in good shape

20" Fir N. $62^{\circ}E$. 9.9

18" Fir S. $25^{\circ}W$. 4.4

Drive 1" I. Pipe for Corner.

Course of Line S. $89^{\circ}49'E$.

Set $\frac{1}{16}$ Cor. Half way at Sta. 1315.0

Set 1" I. Pipe.

Mark 20" Yew N. $36^{\circ}47'E$. 61.7

10" Yew N. $44^{\circ}02'W$. 29.0

South on West line Section 27 ^{#2}

Beg. at Cor. Sec. 21-22-27-28

South Var. 21°

600.0 Top Spur.

2458.0 Cow Creek

5293.0 Cor. Sec. 27-28-33-34

Find 4 Witness Trees as follows.

10" Fir N. $21^{\circ}45'E$. 29.7

16" Fir S. $81^{\circ}30'E$. 20.0

16" Fir N. $45^{\circ}26'W$. 9.5

18" Fir S. $57^{\circ}04'W$. 35.4.

Set 1" I. Pipe for Corner.

Course of Line S. $0^{\circ}15'E$.

Set $\frac{1}{4}$ Cor. half way or at 2696.5

Set 1" I. Pipe 8" below surface.

Mark 30" Cedar N. $8^{\circ}07'W$. 211.2

14" Ash N. $85^{\circ}20'E$. 177.5

Set $\frac{1}{6}$ Cor. at 1323.2

Drive 1" I. Pipe for Corner.

Mark 10" Fir N. $21^{\circ}37'E$. 76.0

16" Fir N. $79^{\circ}53'W$. 195.5

C. S. File No. 40/29

#3

South on $\frac{1}{2}$ Section 27Begin $\frac{1}{4}$ Corner bet. Sec. 22 + 27

1660.0 Small Creek C. S.W.

2500 Leave timber.

4100 enter road.

5185 Mc Ginnis Creek C. W.

5297.5 $\frac{1}{4}$ Cor. bet. 27 + 34. $\frac{1}{4}$ " I. Pipe

No trees available.

Put Center of Section at 2656.4

 $\frac{1}{16}$ Cor. at 1328.2 Drive 1" I.P.Mark 14" Fir N. $52^{\circ}40'E$. 15.812" Fir N. $46^{\circ}W$. 17.2C. S. File No. 40/29

North on East line Section 27

#4

Beg. at Corner Section 26-27-34-35

Find 26" Fir N. 62° W. 23.7

14" Fir N. 75° E. 25.7

15" Cedar S. 40° E. 23.1

Drive $1\frac{1}{4}$ " I. Pipe for Corner.

Mark 10" Fir N. $49^{\circ}55'$ E. 56.2

9" Fir S. $81^{\circ}12'$ E. 49.6

8" Cedar S. $25^{\circ}44'$ W. 34.3

North

340 Top Spur

487 Bottom Draw.

900 Top Ridge.

1530 Creek C. W.

1765.0 Top Spur

2970 McGinnis Cr. C. S. W.

5266.0 Cor. to 22-23-26-27

Find 18" Fir N. $26^{\circ}30'$ E. 28.0

36" Fir S. 89° W. 12.5

Drive 1" I. Pipe for Corner.

Mark 8" Fir S. $19^{\circ}17'$ W. 24.2

16" Fir S. $48^{\circ}30'$ E. 14.5

C. S. File No. 40/29

Place $\frac{1}{4}$ Cor. bet Sec. 26 + 27 half
way bet. Corners. at 2633.0

Drive 1" I. Pipe for Corner.

Mark 12" Yew N. $66^{\circ}52'E$. 27.5

12" Yew N. $61^{\circ}43'W$. 35.5

At 3939.5 put in $\frac{1}{6}$ Corner

Drive 1" I. Pipe in center of Log. Rd.

Mark 34" Fir S. $17^{\circ}48'E$. 11.7

34" Fir S. $66^{\circ}05'W$. 40.8

West on E Section 27

(6)

Beg. at $\frac{1}{4}$ Cor. bet. Sec. 26+27

West

0.75 McGinnis Cr. C.S.

510 Top Spur

550 Logging Rd.

4700 E Rd.

4800 Cow Creek C.W.N.

5250.7 $\frac{1}{4}$ Cor. bet Sec. 27+28

Set Center of Sec. 27 at inter-
section of both center lines.

or at 2629.2 Set 1" I. Pipe

Mark 18" W. Fir N. $37^{\circ}04'W$. 57.8

14" Fir S. $65^{\circ}40'W$. 49.0

$\frac{1}{16}$ Cor. at 1314.6 Drive 1" I. P.

Mark 12" Fir S. $88^{\circ}09'E$. 56.0

14" Fir S. $26^{\circ}W$. 56.5

$\frac{1}{16}$ Cor. at 3939.9 Drive 1" I. P.

Mark 30" Pine N. $60^{\circ}E$. 119.8

12" Fir N. $14^{\circ}05'E$. 94.4