

Route 3, Box 8
Lebanon, Oregon

September 8, 1948

County Surveyor's Office
Douglas County
Roseburg, Oregon

Dear Sir:

On September 3 and 4, I worked in your county and located some corners and rewitnessed two for which I am sending you notes:

¼ corner on North line Sec 4, T 25 S, R 7 W

Govt. Notes:

12" Fir N 37 E 24 lks.
30" Fir S 67 E 24 lks.

Found "¼ S" scribed on remains of 12" fir. This tree is rotten and broken. 30" fir at S 67 E is in good shape. Scars show plainly. I set stake at corner and marked new a 34" Fir at N 52° E 30.5 feet distant from corner. Mkd "CS BT"
"CS ¼".

The govt. notes do not state whether this is a Common Corner with Sec. 4, T 25 S, R 7 W and Sec. 33, T 24 S R 7 W,

Found NE Cor. Sec. 4

Fir 14" S 66 E 19 lks
Cedar 18" S 65 W 19 lks
Fir 14" N 43 E 22 lks
All trees standing in good condition. Stake at corner.

South ¼ corner, Sec. 5, T 24 S, R 6 W.

Govt. Notes

Fir 30" S 26½ E 57 lks.
Laurel 6" N 43½ East 26½ lks.

Bert W. Udell

Ascertained this corner by chopping out stump of 30" Fir. Found "¼ S". Measured N 26½ West 37.62 feet and then North 43½ East 17.5 feet. Found at this point an 8" Madrone. This appeared to be sheet from original tree--remains of which were on East side of sheet. Set stake at corner and marked new a 18" white Fir S 80° E 9.5 ft.
36" " " N 18° W 32.0 ft.

Sincerely yours,

Bert W. Udell

Bert W. Udell
Registered Engineer # 2301

*Present with me
was my helper -
Howard E. Taylor.*