

Sept 17, 1949

DESCRIPTION OF SURVEY FROM THE S.E. CORNER OF SECTION 15 - T 25 S - R 7 W - W.M., DOUGLAS COUNTY, OREGON TO THE MEANDER CORNER ON THE EAST BANK OF THE UMPQUA RIVER BETWEEN SECTIONS 16 AND 21.

Began at a hub previously set 195.73 ft. North and 5291.03 ft. West of the S.E. Corner of Section 15.

Made search for S.W. Corner of Section 15, but find no evidence. Set a 1" x 30" pipe at a point S 89°43' W 5280.0 ft. from the S.E. Corner. Continue Westerly to the vicinity of the 1/4 Corner between Sections 16 and 21 but find no evidence of Corner. Continue Westerly to the Easterly bank of the Umpqua River and make search for Meander Corner at a point 3655.08 ft. West of the N.E. Corner of Section 16 but find no evidence there. Search at the line recognized by local residents and find rotted oak stumps in toe of road fill and oak tree which I believe to be a witness tree. From this evidence I drive a 3/4" x 54" rod at the point believed to be the original location for the Meander Corner and find it is due West from the S.E. Corner of Section 15, and N 89°36' W 3645.5 ft. from the pipe set for the N.E. Corner of Section 16. Marked following witness trees for Meander Corner:

18" Oak S 41° E 9.5 ft.
8" Oak East 108.1 ft.

~~FILED~~
RECEIVED

FEB 15 1950

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.



Rec. 3-14-50
G.L.A.

GLEB No. 40/227

Mar 24, 1949 -

DESCRIPTION OF SURVEY TO LOCATE THE 1/4 SECTION CORNER BETWEEN
SECTIONS 15 and 16 - T 25 S - R 7 W - W.M., Douglas County, Oregon

Began at a pipe in S.E. Corner Section 15 and ran West 5274.75 ft. and North 2699.62 ft. where I find the trunk of a fir tree which answers the description of the original B.T. for this corner although the remains are too rotten to find any scribe or blaze. I locate a point S 10° W 90 lks. as described in the original notes and drive a 1" x 60" pipe and mark the following for witness trees:

24" Red fir	N 65° W	22.0 ft.
6" W. fir	S 10° E	6.0 ft.
18" W. fir	S 56° E	47.0 ft.

The corner being North 2641.12 ft. and West 5285.06 ft. from the S.E. Corner of Section 15. The bearings used are true bearings obtained by solar observation.



~~FILED~~
RECEIVED

FEB 15 1950

COUNTY SUPERVISOR
DOUGLAS COUNTY, ORE.

Rec. 3-14-50
C.L.F.