

See Revised Copy

NARRATIVE OF SURVEY

OF A PARCEL OF GROUND (designated as "A") in
SEC. 30, T.32 S., R.5 W., DOUGLAS COUNTY, OREGON.

This survey was made for Mr. Pirley Winkelman on
Nov. 25, 1950, for the purpose of transferring title.
Used a transit, long band chain and range pole,
Mr. Winkelman and two others helping with the survey.
Bearing of the lines were taken from an observa-
tion on Polaris made on Sept. 5, 1950 at E. Elongation.

Description

Beginning at a point 1307.2 feet east and 1277.5
feet south of the $\frac{1}{4}$ section corner between sections 19
and 30 of T.32 S., R.5 W., thence

S. 89°-58' W. for 379.2 feet, thence

N. 34°-35' W. for 117.6 feet, thence

S. 72°-37' W. for 111.2 feet, to a point on the
NEly bank of Woodford Creek, thence along the Creek bank

S. 29°-36' E. for 117.0 feet, thence

S. 45°-26' E. for 165.4 feet, thence

S. 69°-05' E. for 134.4 feet, thence

S. 52°-32' E. for 75.9 feet, thence leaving the Creek
bank

N. 0°- 08' E. for 148.5 feet, thence

N. 89°-58' E. for 190.0 feet to a point near Barton
Road, thence along side of the road

N. 0°-08' E. for 100.0 feet to the point of begin-
ning.

Area enclosed is 1.776 acres, all in the west half
of the northeast quarter of section 30 township 32 south
range 5 west of the Willamette Meridian, Douglas County,
Oregon.

Corner Stakes

All corner stakes are $\frac{1}{4}$ inch iron pipes 30 inches
long, driven 24 inches into the ground except the point
of beginning which is a drill steel designated by D.S.
on the sketch.

See accompanying sketch for further information.

FILED 1-4-51

RECEIVED

JAN 8 1951

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

COUNTY SURVEYORS FILE DATA
DO NOT REMOVE FROM OFFICE



C.S. File No.

40/297-2

SKETCH of SURVEY
 of 2 PARCELS of GROUND ("A" & "B") in
 W 1/2 of the NE 1/4, SEC. 30, T. 32 S., R. 5 W. W.M.
 for
MR. PIRLEY WINKELMAN



Scale: 1 in. = 100 ft.

Date: Dec. 7, 1950

Surveyed and Sketched by *H. W. Lawrence.*

