

ARTHUR BOYER  
ROSEBURG, OREGON

The following notes are for <sup>1/4</sup> Sec corner established - The quarter section corner between Sec's 7, Twp. 31S; Rg. 1W <sup>and</sup> 82, T31S; Rg 2W; W.M.,

The line was run <sup>South</sup> from the orig sec cor of 1. <sup>9</sup>/<sub>4</sub> 12 T31S; R2W <sup>and</sup> 6 <sup>9</sup>/<sub>4</sub> 7, T31S; R1W., W.M. No sign of the <sup>1</sup>/<sub>4</sub> Sec corner could be found at or near the 2640 ft mark, after a search of three hours, the line was continued south <sup>and</sup> at a point 5425 ft south of the above desc. sec cor, a squared 6" <sup>oak</sup> ~~tree~~ was found on line, it was scribed "S 7 <sup>and</sup> S 12 <sup>and</sup> 18 <sup>and</sup> 13" <sup>and</sup> renewed by a county surveyor, an oak witness tree was found in Secs 7 <sup>and</sup> 18 <sup>and</sup> a pine in 12.

Set <sup>1</sup>/<sub>4</sub> corner, from above, at a point on line midway bet. the two sec. corners <sup>and</sup> 2712.5 ft south of the N.E. Cor 12. - <sup>For corner</sup> <sup>(scribed)</sup> Marked <sup>1</sup>/<sub>4</sub> a 6" maple "S 7 <sup>and</sup> "S 12" "1581" <sup>and</sup> marked (scribed) a 4" maple tree in Sec 12 "S 12 T31S R2W" "1581 BT  $\perp$  N 51  $\frac{1}{2}$ ° W. 15 ft <sup>and</sup> - in Sec 7 - scribed a 12" fir "S 7, T 31S., R1W. 1581 BT" N 48  $\frac{1}{2}$ ° E 15 ft.

Date for above Dec 27, 1950

Witnesses George Henderson <sup>and</sup> Joseph Jenks

Renew

Established by myself.

2-3-51

Arthur Boyer

Note - A conglomerate rock about 35 ft high <sup>and</sup> 20 ft E+W by abt. 40 ft N+S. rises about N 45° E 75 ft from the above estd. cor. this rock is approx 40 ft E of sec. line (Range Line)