

2-13-52

1/4 Section Corner Section
21-28, T305, R4W, W.N.A. as
determined by O.B.T.

A Dead B.O. snag fallen
bears $S 55^{\circ} E$ 215.0' dist.

I chopped out this B.T. & fd. scribe.

At corner point I set
1" x 30" I.P.

from which

A B.O. 7" diam. bears $N 68^{\circ} W$,
112.0' dist. mkd. 1/4 S 21, B.T.

A W.O. 22" diam. bears $S 53^{\circ} W$,
237.0' dist. mkd. 1/4 S, S28,
T305, R4W, B.T.

Fence corner bears $N 68^{\circ} W$,
79.0' dist.

Farm House on Beals Creek,
bears $S 9^{\circ} W$ (Var. $18^{\circ} 30'$)

Corner lies on steep East
slope.

Sec. Cor. 21-22-27-28 bears
East 2522.0'


(OVER)

CS 40/436-11

F-40-386

Witness:
Frank Harrison

Frank Harrison



REGISTERED PROFESSIONAL
ENGINEER
2880
OREGON
NOV. 5, 1948
STATE BOARD OF ENGINEERS, P.E.

FILED
RECEIVED

FEB 23 1952

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

Work done for Frank Harrison

C. S. File No. 40/386