

T29S, R7W.

AT SEC. COR. I FIND
1/8 IN. IRON POST WITH
BRASS CAP, MKD. U.S.
LAND OFFICE, 1924,
T29S, R7W, SPCS,
17-18-19-20
MAGNETIC DECLINAT-
ION AT THIS CORNER
IS: 19°30' E


N 102°3'E, 2563.4 (RECORD)

DESCRIPTION
TO TRU AND IS
THE RECORD BEING
ESTABLISHED DURING
THE SURVEY OF
U.S. LAND OFFICE IN
1924.

SURVEY TO ESTABLISH N. 1/2 OF THE WEST LINE SEC. 20, T29S, R7W, WM.

GRANT & EVANS, ENGINEERS
ROSEBURG, OREGON
SURVEYED MARCH 6-7, 1952, BY
A.R. EVANS, REG. PROF. ENGR
SCALE 1" = 300'

COUNTY SURVEYORS FILE DATA
DO NOT REMOVE FROM OFFICE



1/4 COR

19 20

AT 1/4 SEC. COR, 19-20,
I FIND A 3/4 IN. IRON
POST, WITH BRASS CAP,
MKD, 1/4S - 19-20, U.S.
LAND OFFICE, 1924.
MAGNETIC DECLINATION
AT THIS CORNER IS:
21°00' E.