

ARTHUR BOYER  
ROSEBURG OREGON

SOUTH LINE SEC 30, T. 29 S, R 6 W W M  
April 23-24, 1952

Found the S E corner section 30, The orig rock and wit. trees which are on a flat about 100 ft south of a flowing stream and about N 45°W 75 ft from the site of a homesteader's cabin in section 32, from this cor ran S 89°55'W 2758.0 ft. , retracing a blazed line, probably orig survey, to the south quarter corner of sec 30 where the original rock and witness trees were found this corner is on the side of a 28° slope facing west and about 250 ft east of the bottom of the slope, it is very hard to find all the trees have been burnt although they are standing, mostly, and all are about the same size and height Tacked an aluminum tag on the cedar witness tree which is in sec 30, tag is on the west face of the tree about 6 ft above the ground From here went back to the S W cor of the E 1/2 of the E 1/2 of said sec. and at a point S.89°55'W 1379.0 ft from the S E cor. of said sec 30, set a steel jeep axle with flange on top, this corner is on a flat about 15 ft. above and 75 ft. E. about, from a through road which is surfaced, there is a fir tree 13" dia with a board nailed on it which was previously taken for this corner, it is about 40 ft, N.45°W from the true corner of this forty From here went to the approx location of the S W corner of this sec 30 On a through road at the top of a ridge where the ridge flattens out ( n & s ridge) found the laurel wit tree which was originally growing in sec 36, T 29 S R.7 W This tree was rooted out by a bulldozer recently and laying on the side of the newly graded road After about an hours search the root hole for this tree was found and from there the approx sec cor. was located and then the only standing witness tree was found, the laurel in section 30 which was dead and about to fall, the sec. corner was set from this tree and the following bearing trees were marked

S W cor. 30, 29/6

24" Fir, N 89°30'E 18.5 ft marked "S.30 T 29 S, R 6 W B.T 1581

18" " S 56°E 73 ft, bark blaze, "S 31 " "

18" " N 27°30'W 79 ft " " "S 25 T 29 S, R 7 W " "

23" Fir Stump, no close tree, S 56°30'W 75 ft marked "S 36 T.29S R 7 W, B T. on root of stmp just above ground surf

The above corner is about 15 ft east of the newer graded through road, about 2 ft below the road bed, there was an older road abt 100 ft east which has been abandoned the corner is marked with a squared laurel marked S.30, S31, S25, S 36 and there is an aluminum tag on the wit. tree in sec 30. on the N side of tree.

From here retraced the old orig blazed line on S. side sec. 30, N.89°55'E to the S quarter corner of said sec. 30

witnesses for above corner renewal

Frank Smith

D B Lewis

Mr Hollenback

renewed Apr. 24, 1952.

FILED   
REL, Arthur Boyer

APR 26 1952

ROSEBURG OREGON  
SOUTH LINE SEC 30

C. S. File No. 41/24 A

