

Claude Kerr Cruising and Engineering Service

REGISTERED PROFESSIONAL ENGINEER

Real Estate

PHONE 3-3751

2430 FOOTHILL DRIVE

ROSEBURG, OREGON

FILED
June 6, 1953 RECEIVED

JUN 8 1953

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

Mr. Ben Irving
County Surveyor
Roseburg, Oregon

Dear Sir:

I recently reset the following corners in Township 30 South,
Range 7 West.

The corner for Sections: 13, 24, ¹⁹ ~~25~~, and 18.

I found two original Black Oak BT's; one bearing,
South 60° West for 327 Links, which is now a 4 1/4" tree.
The other bears North 70° East for 70 Links and is now as 38" Black Oak.

I set 3"x3"x4 1/4" Cedar Stake for the corner from the original Bearing
Trees, marking it S 13, S24, S7, and S18.

Quarter corner for Sections 24 and 19 on township line.
Found the original Incense Cedar BT, bearing North 20° East for
126 Links. Chopped in and found old scribe markings. This is
now a 2 1/4" Cedar.

Set a Cedar stake for the 1/4 corner and marked it 1/4 S24 and 1/4 S19.

Quarter corner for Section 23 and 24.

Started at the established corner for 13, 14, 23, and 24. Chained South
on random for 2640 feet, using a variation of 20°30' East, and looked thoroughly
for the old BTs for this 1/4 corner, but did not find them; continued on the random
line to the South boundary of Section 24, hitting 578' East of the corner for
Section 23, 24, 25, and 26.

The correct variation was found to be 14° 18' East. The West side
of Section 24 is 5363.0 feet. I set a stake for the 1/4 corner on correct
line at the halfway point or 2681.5 feet south of the NW corner.

Two BTs were marked:

A 9" Fir, bearing North 3° East for 8.0 feet, marked 1/4 S 24.

A 13" Fir, bearing South 24° West for 39.8 feet, marked 1/4 S 23.

Yours very truly,

Claude Kerr
CLAUDE KERR

P.S., Also, Quarter corner for Secs. 13 & 24,
T30S, R7W. I found the original 60" Laurel BT, bearing N 65° E. for 39 Lks. Set a 4"x4 1/4" Cedar
Stake for 1/4 corner stake marking it 1/4 S13 and 1/4 S24. The other BT has been destroyed.

CK.

CS 41/160