

NOV 23, 1953

1/4 COR S 7 & 8 T. 29S, 12.6W.

AT COR POINT FOUND OLD
SCRIBED STAKE & ROOT HOLE OF
OLD OAK WHICH HARRISON RICE SINGERS
IS THE POSITION OF OLD OAK B.T.

AT COR POINT.

SET 3/4" X 36" IRON PIPE WITH
4" X 4" X 36" FIR POST ALONG SIDE, FROM WHICH
ROOT HOLE BEARS S 18° W, 17 LIES

NEW B.T.S

12" FIR BEARS S 69° E 38 FT

14" FIR BEARS S 72 1/2° W 25 FT

WITNESS: CLYDE JOHNSON
WORK DONE FOR CLYDE JOHNSON

Gene E. Johnson

44/248-1

I, Harrison Rice, do hereby certify that the $\frac{1}{4}$ Section corner of Sections 7 & 8, T29S, R6W, W. M. as re-established by Gene E. Johnson, a Registered Professional Engineer in the State of Oregon is in the same position as that occupied by the original government corner.

Signed

Harrison Rice
Harrison Rice

Gene E. Johnson

NOV 23 1953

$\frac{1}{4}$ CORNER S 788, T. 29S., R. 6W., W.M.

AT CORNER POINT I FIND AN OLD SCRIBED POST LYING IN FENCE LINE, AND HOLE IN GROUND CONTAINING OAK ROOTS, WHICH HARRISON RICE SWEARS IS THE POSITION OF THE BEARING TREE FOR SECTION 7, T. 29S., R. 6W., W.M. WHICH WAS A DEAD 14" OAK, AND WAS DESTROYED IN PROCESS OF BUILDING FENCE. TREE HOLE BEARS S 18W, 17 LINKS FROM CORNER POINT.

AT CORNER POINT:

SET $\frac{3}{4}$ " X 30" GALVANIZED IRON PIPE WITH 4" X 4" X 36" SCRIBED FIR STAKE ALONG SIDE FROM WHICH:

NEW B.T.'S

12" FIR ^{BEARING} S 69° E 382 FT

14" FIR ^{BEARING} S 72 $\frac{1}{2}$ ° W 255 FT.

WORK DONE FOR CLYDE JOHNSON

WITNESS: CLYDE JOHNSON