

GILBERT A. GARDNER

REGISTERED SURVEYOR
COTTAGE GROVE, OREGON

OFFICE: 709 MAIN STREET
RESIDENCE: 1643 W. MAIN STREET

Mr. Ben B. Irving
Douglas County Surveyor
Roseburg, Oregon

Dear Mr. Irving:

Enclosed are notes on recent corner renewals. Some are in Lane County, but are in the same area so thought they should be kept together.

Thanks,


Gil Gardner

FILED
RECEIVED

JUL 17 1954

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

June 2, 1954
J. F. Woodard
Gilbert Gardner

Section corner for Sections 17, 18, 19 & 20, Township 23 South, Range 3 West, W. M.

New trees marked:

6" Alder brs N 04° E 2.0 feet, marked S17BT
6" Alder brs N 75° W 14.2 feet, marked S18BT
8" Alder brs S 45° W 14.9 feet, marked S19BT
6" Alder brs S 54° E 21.5 feet, marked S20BT

Placed steel axel in ground at location of old corner, as located and preserved by John F. Woodard

1/4 corner between Sections 20 and 21, Township 23 South, Range 3 West.

Stake in stump on hemlock tree previously marked for corner; scribing visible in said stump.

Marked new trees:

16" Hemlock brs N 75° E 22.5 feet, marked 1/4 S BT
8" Cedar brs S 73° E 90.0 feet, marked 1/4 S BT

No other tree available.

REGISTERED
OREGON
LAND SURVEYOR

GILBERT A. GARDNER
NOV. 9, 1951
276

1/4 corner between Sections 21 and 22, Township 23 South, Range 3 West.

New bearing trees:

18" Douglas Fir brs S 11° E 7.8 feet, marked 1/4 S BT.
(original SE bearing tree cut, now 38" stump)
10" Incense Cedar brs N 41° W 39.2 feet

This corner is 100 feet east of rock quarry and approximately 60 feet above logging road on north side.

Section corner for Sections 27 and 28, 21 and 22, Township 23 South, Range 3 West, W. M.

Placed by J. F. Woodard at location of old corner. Found by tearing apart old stump in which scribe marks were visible, and which John F.

FILED
RECEIVED

JUL 17 1954

COUNTY SURVEYOR
DOUGLAS COUNTY, OREGON

(Sec 27, 28, 21 & 22 T 23 S R 3 W - Cont'd.)

Woodard showed to me, and after examining same, remains of scribing were still visible.

Marked new bearing trees:

20" Hemlock brs S 78° E 18.2 feet, marked S27BT
18" Hemlock brs N 85° E 16.2 feet, marked S 22BT
60" Cedar brs S 65° W 12.0 feet, marked S28BT
20" Hemlock brs N 85° W 28.9 feet, marked S21BT

Corner for Sections 28, 29, 20 & 21, Township 23 South, Range 3 West, W.M.

Found stump marked for corner with parts of scribe plainly visible. Re-marked trees as follows:

24" Douglas Fir brs S 34° W 18.5 feet
18" Douglas Fir brs S 41° E 28.0 feet
20" Douglas Fir brs N 33° E 24.0 feet
24" Fir brs N 86° W 23.0 feet

1/4 corner between Sections 29 & 30, Township 23 South, Range 3 West.

39.0 feet North 75° East from yellow tag on bearing stump to 38" Douglas Fir stump and 48" cedar stump bears South 88° West 53.0 feet.

Section corner for Sections 29, 30, 31 and 32, Township 23 South, Range 3 West.

Southwest hemlock bearing tree chopped out; scribe plainly visible.
Cedar and Northeast hemlock located. hemlock still standing,
but nearly dead; bears visible scars.

New bearing trees marked:

16" cedar brs N 74° W, 52.5 feet, marked S30BT
32" cedar brs S 28° W 65.0 feet, marked S32BT
18" hemlock brs 30° W 51.4 feet, marked S31BT
20" cedar brs N 27° E 80.5 feet

7
6
FILED
RECEIVED

JUL 17 1954

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

REGISTERED
OREGON
LAND SURVEYOR

GILBERT A. GARDNER
NOV. 9, 1951
276

C. S. No. 41/286

1/4 corner between Sections 31 and 32, Township 23 South, Range 3 West.

Rescribed original 15" Douglas Fir 6.6 feet East of corner.

50" Douglas Fir brs. S 28° W 18.0 feet.

1/4 corner between Sections 29 and 32

Stump of tree marked for corner has yellow tags set by J. F. Woodard.
Remarked stump: 1/4 BT

1/4 corner between Sections 25 and 36, Township 23 South, Range 4 West.

Found stake from which 8" cedar brs S 70° E 15.0 feet, marked 1/4SBT
Marked one 10" hemlock which brs N 52° E 6.6 feet

Section corner for Sections 25, 26, 35 and 36.

Set 4x4x4' stake. 6" original tree cut; markings indicate scribing;
also cruiser marks on surrounding trees and old stakes at corner point.

Scribed new trees:

12" Douglas Fir brs N 66° 22.1 feet
12" Madrona brs S 39° E 63.0 feet
30" Incense Cedar brs S 76° W 92.7 feet
12" Douglas Fir brs N 06° W 60.5 feet

FILED
RECEIVED

JUL 17 1954

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

