

T 29 S R 5 W

N  $\frac{1}{16}$  SEC. 5 16  $\frac{1}{15}$

SET CORNER AT PROPORTIONATE  
DISTANCE ON LINE BETWEEN  $\frac{1}{4}$  SEC.  
COR. AND SEC. COR.

CORNER FALLS ON STEEP  
BARE ROCK SLOPE. MARKED  
X ON ROCK FOR CORNER. SET  
 $\frac{7}{8}$ " IRON ROD IN ROCK CREVICE  
7.3 FT. EAST OF TRUE CORNER.

BLAZED & SCRIBED 2 B.T.'S

24" W. OAK S  $75^{\circ}$  W 99.4 FT.

MKD N  $\frac{1}{16}$  S 16 B.T.

24" FIR S  $50^{\circ}$  E 109.4 FT.

MKD N  $\frac{1}{16}$  S 15 B.T.

DISTANCES MEASURED TO CENTER  
OF TREE. ON BOTH TREES PLACED  
COPPER TAG RE-2741

WITNESS

Miss E. Coffey

A. P. Jones

G.S. File No. 41/300

W  $\frac{1}{16}$  SEC  $\frac{10}{15}$  T29S R5W

SET  $\frac{7}{8}$ " IRON ROD FOR COR.  
AT PROPORTIONATE DIST. ON LINE  
BETWEEN  $\frac{1}{4}$  SEC. COR. & SEC. COR.

BLAZED & SCRIBED B.T.'s

36" MADRONE N  $31\frac{1}{4}^{\circ}$  E 65.0 FT.  
MEASURED TO CENTER OF TREE

SCRIBED W  $\frac{1}{16}$  S 10 B.T.

30" MADRONE S  $10^{\circ}$  E ~~43.0 FT~~  
MEASURED TO FACE OF BLAZE

SCRIBED W  $\frac{1}{16}$  S 15 B.T.

ON BOTH TREES PLACED COPPER  
TAG - RE 2741

WITNESS

Milo E. Jeffrey

*[Signature]*

C.S. File No. 41/300

CENT. W  $\frac{1}{16}$  SEC. 15 T29S R5W

SET  $\frac{7}{8}$ " IRON ROD FOR CORNER  
AT PROPORTIONATE DISTANCE  
ON LINE BETWEEN CENT.  $\frac{1}{4}$  SEC.  
& WEST  $\frac{1}{4}$  SEC. 15.

BLAZED & SCRIBED 2 B.T.'s  
 $\frac{1}{6}$ " MAPLE S  $12\frac{1}{2}^{\circ}$  W 30.3 FT.  
MK'D C-W  $\frac{1}{16}$  S 15 B.T.

8" FIR N  $0\frac{3}{4}^{\circ}$  W 95.3 FT.  
MK'D C-W  $\frac{1}{16}$  S 15 B.T.

DISTANCES MEASURED TO CENTER  
OF TREES. ON BOTH TREES PLACED  
COPPER TAG R.E. - 2741

WITNESS

*Wm. C. Gaffney*

*Arthur L. Gowan*

$\frac{1}{4}$  SEC. 15 ~~14~~ T 29 S R 5 W

FOUND ORIGINAL B.T.'s

10" W. OAK N 65° W 78 ~~ft.~~

STILL ALIVE AND STANDING  
SCAR OF BLAZE PLAINLY VISIBLE  
TREE ROTTEN IN HEART - NO  
SCRIBE MARKS FOUND

STUMP OF 14" W. OAK N 68° E  
51 LKS. SCRIBE MARKS PLAINLY  
VISIBLE.

AT LOCATION OF CORNER FOUND  
CEDAR STAKE SCRIBED  $\frac{1}{4}$  S. C. S.

SET  $\frac{7}{8}$ " IRON ROD FOR COR.

BLAZED & SCRIBED 2 B.T.'s

20" FIR N 44  $\frac{3}{4}$ ° W 16.2 FT

M'D  $\frac{1}{4}$  S 15 B.T.

15" W. OAK S 55  $\frac{1}{2}$ ° E 93.7 FT.

M'D  $\frac{1}{4}$  S 14 B.T.

DISTANCES MEASURED TO CENTER  
OF TREES. ON BOTH TREES PLACED  
COPPER TAG RE-2741

WITNESS

W. E. ~~W. E. W. E.~~

*A. R. Swan*

C. S. File No. 41/300

CENT.  $\frac{1}{4}$  S 15 T29S R5W

SET 1" IRON POST 36" LONG  
WITH BRASS CAP M'KD T29SR5W  
C  $\frac{1}{4}$  S 15 RE-2741 30" IN  
GROUND WITH MOUND OF ROCKS  
AT INTERSECTION OF LINES  
JOINING E. & W.  $\frac{1}{4}$  SEC. COR'S  
AND N. & S.  $\frac{1}{4}$  SEC. COR'S.

BLAZED & SCRIBED 2 B.T.'S  
24" W. OAK N 82°W 305.5 FT.  
MEASURED TO CENTER OF TREE  
M'KD - C  $\frac{1}{4}$  S 15 B.T.

6 FT CLUMP OF MYRTLE  
N 47°E 274 0 FT. MEASURED  
TO FACE OF BLAZE. SCRIBED  
C  $\frac{1}{4}$  S 15 B.T.

ON BOTH TREES PLACED  
COPPER TAG R.E.-2741.

WITNESS

Wils E. Jeffrey

A. R. Evans

$\frac{1}{4}$  SEC 16~~15~~ T29SR5W

SET  $\frac{7}{8}$ " IRON ROD FOR COR.  
AT PROPORTIONATE DISTANCE ON  
LINE BETWEEN SECTION CORNERS

BLAZED & SCRIBED 2 B.T.'S

18" FIR N  $63\frac{1}{2}^{\circ}$  W 38.2 FT.

MKD.  $\frac{1}{4}$  S 16 B.T.

12" FIR N  $26\frac{1}{2}^{\circ}$  E 22.9 FT.

MKD.  $\frac{1}{4}$  S 15 B.T.

DISTANCES MEASURED TO CENTER  
OF TREE. ON BOTH TREES PLACED  
COPPER TAG RE 2741

WITNESS

Milo E. Gouffey

AR Bauer

~~1/4~~ SEC. ~~10~~/~~15~~ T29S R5W

SET  $\frac{3}{4}$  IRON PIPE IN MOUND  
OF ROCK FROM 2 O.B.T.'s FD.  
8" W. O. N  $64^{\circ}$  E 136.0 FT.  
12" W. O. S  $70^{\circ}$  E 119.6 FT

BOTH O.B.T.'s ALIVE AND IN  
GOOD CONDITION.

BLAZED AND SCRIBED 14" ALDER  
S  $4\frac{1}{2}^{\circ}$  W 97  $\frac{1}{2}$  FT. SCR.  $\frac{1}{4}$  S 15 BT.  
MEASURED TO CENTER OF TREE

ON ALL 3 TREES PLACED COPPER  
TAG - RE 2741

WITNESS

Milo E. Godfrey

A. R. Owens

C.S. File No. ~~41~~/300

(CITY OF MYRTLE CREEK)