

Claude Kerr Cruising and Engineering Service

REGISTERED PROFESSIONAL ENGINEER
2-1722 Real Estate
PHONE ~~3581~~ 2430 FOOTHILL DRIVE
ROSEBURG, OREGON

November 16, 1954

Mr. Ben Irving
County Surveyor
Roseburg, Oregon

Dear Sir:

I re-set the following corners on the range line between T25S, R7W, and T25S, R8W.

1. 1/4 corner for Sections 7 and 12.
Found the original Oak B. T., now 37" in diameter, bearing N. 6°30' W. for 810 Lks. Chopped in and found BT scribe marks. Refaced the tree and marked it with 1/4 S 12 BT. I set a Cedar corner stake for the 1/4 corner with a 1/2" pipe alongside.
Marked a new BT. On the North side of the county road. A 2 1/4" Oak, bearing S. 89° E. for 239.5 feet. Marked 1/4 S 7 BT.
2. Witness Corner a line between Sections 7 and 12 at 58.95 chains South. Found the original Fir BT, now 50" in diameter, bearing S 80° E. for 10 Lks. (Marking still visible.)
Reset the Witness Corner from this BT setting a 4"x4" stake, which I scribe W. C. on the east and West faces, and 58.75 Chs. S. on the North face. Marked a new witness tree. A 1 1/4" Red Cedar, bearing N. 55° W. for 19 feet and marked W. C. S. 12 BT.
The 1/4 corner for 7 and 12 can be seen from the W. C. at 58.95 chains South. The correct variation between these corners is 20°20' East.

Yours truly,

Claude Kerr
Claude Kerr

FILED
RECEIVED

NOV 18 1954

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

FILED
RECEIVED

NOV 18 1954

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

CS FILE 411316