

COR. SECS $\frac{11}{14} \frac{12}{13}$ T 23 S R 5 W

FOUND STUMP OF O.B.T. 16" FIR
S 49° W 124 LKS. FD. OLD FACE - TOO
BADLY ROTTED - NO SCRIBE MARKS VISIBLE
FD. STUMP HOLE O.B.T. 16" FIR
N 88° E 56 LKS.

FD. COR. SET BY LITTRILL FOR W $\frac{1}{16}$ COR.
S 88° 08 $\frac{1}{2}$ ° E 1292 FT. - USING SLOPE
DISTANCE THIS MAKES DIST. FROM SEC.
COR. AGREE WITH LITTRILL'S DIST. IF I
USE HORIZONTAL DISTANCE FROM
LITTRILL'S COR. TOPOGRAPHY OF SEC.
COR. WILL NOT FIT TOPOGRAPHY AS
CALLED FOR IN GOV. FIELD NOTES.
AFTER RUNNING TO N.E. COR. SEC. 13 AND
WEST $\frac{1}{4}$ SEC. COR. SEC. 13 I DECIDE TO USE
EVIDENCE OF OLD B.T.'S EVEN THOUGH
NO SCRIBE MARKS FOUND.

SET $\frac{3}{4}$ " ROD IN MOUND OF ROCKS 3 FT.
X 2 FT. HIGH. FOR COR.

BLAZE & SCRIBE 4 NEW B.T.'S

16" FIR N 19° W 46.9 FT MKD T 23 S R 5 W
S 11 BT

6" MADRONE N 47° 15' E 47.8 FT.
MKD T 23 S R 5 W S 12 BT

16" FIR S 60° 30' E 28.6 FT.
MKD T 23 S R 5 W S 13 BT

14" MADRONE S 36° W 33.0 FT.
MKD T 23 S R 5 W S 14 BT

ON ALL TREES PLACE COPPER TAG RE 2741

WITNESSES

GENE E JOHNSON
MILD E. GARDNER

C. S. File No. 44/318-4