

For the standard Cor. of Secs. 35 & 36, Tp. 32 S, R8W, W.M. no evidence of the Cor. post remains. True point for Cor. established from original bearing trees: A Fir stump, 30 ins. diam., bears N.  $31^{\circ} 46'$  E., 9.4 ft. dist., and old notch and a (B.T., carved with knife) are all that remain. A fir stump, 21 ins. diam., bears N.  $49^{\circ} 08'$  W., 23.2 ft. dist., this stump badly rotted out. A fir, 26 ins. diam., bears S.  $9^{\circ} 39'$  E., 12.6 ft. dist., parts of original scribing visible. At the point for the Cor. I drive  $1\frac{1}{4}$ " iron pipe 30" long, 24" in the ground, and take new bearing trees as follows:

A Fir, 11 ins. diam., bears N.  $27^{\circ} 24'$  E., 14.7 Ft. dist. Marked 3642 B.T.

A Fir, 14 ins. diam., bears N.  $33^{\circ} 27'$  W, 17.4 Ft. dist. Marked 3642 B.T.

A Live Oak, 17 ins. diam., bears S.  $0^{\circ} 13'$  W, 31.4 Ft. Dist., Marked 3642 B.T.

From this corner N.  $1^{\circ} 26' 42''$  W. on a random line between Secs. 35 & 36, I find no trace of the  $\frac{1}{4}$  Cor. & continue on to the Cor. of Secs. 25, 26, 35, & 36 at 5096.1 Ft.; I fall 92.3 Ft. West of this corner. At the true point for the Cor. established from the four original bearing trees, drive a  $1\frac{1}{4}$ " iron pipe, 30 ins. long, 24 ins. in the ground. Thence, S  $0^{\circ} 24' 22''$  East on a true line between Secs. 35 & 36; at 1274.0 Ft. drive a  $1\frac{1}{4}$  in. iron pipe 30 in. long 24 in. in the ground for the 1/16 Cor., from which:

A Madrone, 32 ins. diam., bears N.  $72^{\circ} 50'$  E., 45.9 Ft. dist.

A Fir, 28 ins. diam., bears N  $89^{\circ} 17'$  W, 49.5 Ft. dist. at 2548.1 Ft. drive a  $1\frac{1}{4}$  in. iron pipe 30 in. long 24 in. in the ground for the  $\frac{1}{4}$  Cor. Secs. 35 & 36, from which:

A Fir, 8 ins. diam., brs. S.  $82^{\circ} 39'$  E, 36.4 Ft. dist.  
A Fir, 15 ins. diam., brs. S.  $76^{\circ} 59'$  W, 36.2 Ft. dist.  
At 3822.1 Ft. drive a  $1\frac{1}{4}$  in. iron pipe 30 ins. long 24 in. in the ground for the 1/16 Cor., from which:

A Fir, 12 ins. diam. brs. S.  $29^{\circ} 37'$  E., 103.0 ft. dist.  
A Madrone, 9 ins. diam., brs. S  $7^{\circ} 17'$  W, 90.5 ft. dist.  
5096.1 ft. the standard corner Secs. 35 & 36.



All Bearing Trees Marked 3642 B.T.

FILED  
RECEIVED

November 22, 1954

DEC 1 1954

COUNTY SURVEYOR  
DOUGLAS COUNTY, ORE.

41/320