

ARTHUR BOYER
ROSEBURG, OREGON

Jan 21, 1955

FILED
RECEIVED

JAN 21 1955

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

County Surveyor,
Roseburg, Ore.

Dear Ben,-

Following are notes of a 1/16th corner which I set yesterday in the vicinity of the county road between Canyonville and Riddle.

Jan. 20th, 1955

Sixteenth corner between the SW 1/4 of section 29, and the NW 1/4 of section 32, T. 30 S; R. 5 W; W.M.

Started the survey at the iron pipe established by Wenderoth at the 1/4 sec. cor bet. secs 29 and 32 and ran westerly on a needle bearing finding the iron pipe for the sec. cor. common to secs. 29, 30, 31 and 32 on a bearing of N.88°-33'W. 2687.0 ft; using a dec. of 20°. The sky was cloudy during the running of this line. The iron pipe set by Wenderoth is abt 2.0 ft. N. of a fence cor. the fence which runs to this cor. from the E. ends here and then turns S. (section cor.) The iron pipe last referred to is the sec. cor pipe. The sixteenth cor. referred to above, was set midway bet the 1/4 cor. and the sec. corner on at 1343.5 ft. A 4" x 4" oak post was driven at this cor. and a pile of rocks mounded up about 18" high and abt. 3 ft. wide, a 12" fir S.82°W. was scribed on the bark, "1/16 S. 32 1581 B.T; and a 15" black oak was scribed in the wood it is N.75°E. 19 ft and marked 1/16 S. 29 1581 B.T. This corner is about 35 ft. S. of the highest rocky point on the hillside which slopes at about 25° a quarter of a mile to the county road to the S. At a distance of 26.5 ft. N.88°33'W. from this 1/16th cor there is a standing old growth 30 inch red fir tree which has a blaze on its E. and W. sides which look like the original blazes. The line was blazed bet. the 1/4 corner and this estd. 1/16 cor. Jan 20, 1955

Arthur Boyer
William Howard, Witness

A.B.

Arthur Boyer

C. S. File No. 41/333

CONDITION
REPORT ONLY
FILED IN
C.S. 613
(COPY ATTACHED)
D.F.
12/79

Started the survey at the iron pipe established by Wenderoth at the $\frac{1}{4}$ sec. cor bet. secs 29 and 32 and ran westerly on a needle bearing finding the iron pipe for the sec. cor. common to secs. 29, 30, 31 and 32 on a bearing of N.88°33'W. 2687.0 feet; using a dec. of 20°. The sky was cloudy during the running of this line. The iron pipe set by Wenderoth is abt 2.0 ft. N. of a fence which runs to this cor. from the E. ends here and then turns S. (section corner). The iron pipe last referred to is the section corner pipe.

The sixteenth corner referred to above, was set midway bet. the $\frac{1}{4}$ corner and the sec. corner or at 1343.5 feet. A 4" x 4" oak post was driven at this cor. and a pile of rocks mounded up about 18" high and abt. 3 ft. wide, a 12" fir S.82°W, was scribed on the bark, "1/16 S. 32 1581 B. T.; and a 15" black oak was scribed in the wood it is N.75°E. 19 ft and marked 1/16 S. 29 1581 B. T. This corner is about 35 ft. S. of the highest rocky point on the hillside which slopes at about 25° a quarter of a mile to the county road to the S. At a distance of 26.5 ft. N.88°33'W. from this 1/16th cor the re is a standing old growth 30 inch red fir tree which has a blaze on its. E. and W. sides which look like the original blazes. The line was blazed bet. the $\frac{1}{4}$ corner and this estd. 1/16 cor. Jan 20, 1955.

Arthur Boyer

William Howard, Witness

FOUND CONDITION REPORT ONLY
 1/24/73
 W/HG
 E 31 RSW

FD.

A NEEDLE ROCK PIT

A ROOTHOLE BEING S 82° W

13.2 FT. WITH A TIPPED OUT 12" FIR ALONGSIDE VISIBLE BARK SCRIBING "BT 1/16 SEC 1581"

A ROOTHOLE BEING N. 75° E, 19.7 FT. (REC. 19 FT) WITH A 16" STUMP ALONGSIDE, PARTIALLY ROTTED WITH VISIBLE SCRIBING.

A 30 IN. FIR STUMP BEING N 88° W 27 FT. NO BARKS VISIBLE, STUMP CUT TOO LOW.

A 20-30 IN. FIR TREE BEING S 83° E APPROX. 20 FT - FIRST FIR IN FLAKE IN HIST. OF COR.

KAREN REED
 C. S. File No. 6/13

C. S. File No. 41/333

COPY FOR FILE 41/333