

Grants Pass, Oregon.  
May 2, 1955.

Mr. Ben B. Irving,  
County Surveyor,  
Douglas County,  
Roseburg, Oregon.

Dear Sir:

The following re-habilitation of the  $\frac{1}{4}$  sec. cor. of secs. 20 and 21, T. 31 S., R. 3 W., Willamette Mer., Oregon, was made by me at the request of Dollar and Patterson Co., Inc., of Glendale, Oregon. Kindly include this description in your records.

---

The  $\frac{1}{4}$  sec. cor. of secs. 20 and 21, T. 31 S., R. 3 W., Willamette Mer., Oregon, is monumented with a basalt stone, 12x6x5 ins. above ground, firmly set, mkd.  $\frac{1}{4}$  on W. face; from which the remains of original bearing trees:

A burnt hemlock, 16 ins. diam., bears S.54 $\frac{1}{2}$ °E., 44 $\frac{1}{2}$  lks. dist., on which no marks remain.

A burnt yew, 12 ins. diam., bears S.74 $\frac{1}{2}$ °W., 31 lks. dist., on which no marks remain.

And new bearing trees:

A hemlock, 15 ins. diam., bears S.72 $\frac{1}{2}$ °E., 60 lks. dist., mkd.  $\frac{1}{4}$  S21 RS33 BT.

A yew, 12 ins. diam., bears N.89°W., 76 lks. dist., mkd.  $\frac{1}{4}$  S20 RS33 BT.

Against N. side of stone, set an iron pipe, 3 ft. long,  $1\frac{1}{2}$  ins. diam., 28 ins. in the ground, mkd. RS33.

---

REGISTERED  
OREGON  
LAND SURVEYOR

*Norman D. Price*

JULY 7, 1944  
NORMAN D. PRICE  
No. 33

FILED  
RECEIVED

MAY 4 1955

COUNTY SURVEYOR  
DOUGLAS COUNTY, ORE.

C. S. File No. 41/314