

SUBDIVISION OF SECTION 24
T. 25 S., R. 2 W., W. M.
BY V. W. HOSFORD, R.P.L.S. NO. 253
FOR EVANS PRODUCTS COMPANY

Preparatory to logging operations in that area, Evans Products Co. sought to establish the boundaries of their properties in Sec. 24, T. 25 S., R. 2 W., W. M.

This survey was made by the method of running angular random lines between the different established corners. A transit was used for measuring the angles, all of which were doubled. All distances were measured with a 300 ft. steel tape and all vertical angles measured by the transit. Bearings were determined by solar observations. Magnetic variation is approximately $21^{\circ}00'$ in this vicinity.

Beginning at corner $\frac{24}{25}/30$ which is a $1\frac{1}{2}$ " iron pipe marked and witnessed as described in the notes of my survey of 1950, and running thence N. $83^{\circ}43'$ W. on a true line between sections 24 & 25.

At 2693.3 ft. I find the original $\frac{1}{4}$ corner between sections 24 & 25. This corner is a marked stone with both bearing trees as described in the original field notes standing and alive.

Thence I run S. $89^{\circ}25'$ W. on true line between sections 24 & 25.

At 1335.1 ft. I established the W. $1/16$ S. 24 & 25.

At this corner I set a 4" hemlock post marked W. $1/16$ S. 24-25 253, from which;

A cedar 24" in diam. bears N. $88\frac{1}{2}^{\circ}$ E. 37.3 ft.
marked W. $1/16$ S. 24 253 B.T.

A cedar 24" in diam. bears S. 4° E. 18.6 ft.
marked W. $1/16$ S. 25 253 B.T.

At 2670.2 ft. the corner common to sections 23, 24, 25, & 26. At this corner I found the original marked stone and four bearing trees as described by the surveyor general, all living except S. E. B. T. which is dead but standing.

FILED
RECEIVED

OCT 4 1955

C. S. File No 42/20-A

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

Thence I run N. 0°24' E. on true line between sections 23 & 24.

At. 1336.1 ft. I established the S. 1/16 S. 23 & 24.

At this corner I set a 4" hemlock post marked S. 1/16 S. 23-24
253, from which;

A hemlock 10" in diam. bears N. 70° E. 2.9 ft.
marked S. 1/16 S. 24 253 B.T.

A hemlock 12" in diam. bears S. 66° W. 19.2 ft.
marked S. 1/16 S. 23 253 B. T.

At 2672.3 ft. I found the original $\frac{1}{4}$ corner between sections 23
& 24. At this corner I found the original marked stone and two bear-
ing trees as described in the field notes. The B. T. for section 23
is dead but standing, the one for section 24 alive.

Thence I run N. 0°26' E. on true line between sections 23 & 24.

At 2627.5 ft. I re-established the corner common to sections 13,
14, 23, & 24. This corner was re-set from the bearing tree in section
14, alive and standing, and the bearing tree in section 24, dead but
with scribing visible. The other two B. T.'s were not found.

Thence I run S. 89°05' E. on true line between sections 13 & 24.

At 1319.9 ft. the W. 1/16 S. 13 & 24, described in the notes of
my survey of 1953.

At 2639.8 ft. the original $\frac{1}{4}$ corner between sections 13 & 24.

At this corner I found the original marked stone and two bearing
trees alive and standing.

Thence I run S. 86°43' E. on true line between sections 13 & 24.

At 2649.3 ft. the corner $\frac{13}{24}/19$, which is a 2" iron pipe with
steel cap marked and witnessed as described in the notes of my
survey of 1950.

From these notes and from the notes of my survey of the east
boundary of section 24 in 1950, I computed the bearing and length
of all the sub-divisional lines of section 24 as shown on the accom-
panying plat.

At mid-point between the corner $\frac{24}{25}/30$ and the East $\frac{1}{2}$ S. 24,
which is on a line bearing N. 0°13' W., and distant 1343.2 ft. from

FILED
RECEIVED

OCT 4 1955

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

See
LAST PAGE →

each, I established the S. 1/16 S. 24 & 30, for section 24 only. At this corner I set a 4" cedar post marked 1/16 S. 24, from which;

A fir 16" in diam. bears S. 53° W. 31.2 ft.
marked 1/16 S. 24 P. S. 253 B.T.

A cedar 24" in diam. bears N. 11½° W. 64.3 ft.
marked 1/16 S. 24 P.S. 253 B.T.

From this corner I run N. 85°29' W. on the south boundary of N. E. ¼ of the S. E. ¼ of section 24.

At 1338.7 ft. I established the S. E. 1/16 S. 24.

At this corner I set a 4" hemlock post marked S. E. 1/16 S. 24, from which;

A cedar 14" in diam. bears N. 74° E. 25.9 ft.
marked 1/16 S. 24 P.S. 253 B.T.

A cedar 30" in diam. bears S. 47½° E. 19.0 ft.
marked 1/16 S. 24 P.S. 253 B.T.

Thence I run N. 0°02' W. on the N. & S. center line of the east ½ of section 24.

At 2650.7 ft. I established the N. ^E(W.) 1/16 S. 24. At this corner I set a 4" cedar post marked 1/16 S. 24 P.S. 253, from which;

A fir 8" in diam. bears S. 17½° E. 14.8 ft.
marked 1/16 S. 24 P.S. 253 B.T.

A hemlock 16" in diam. bears N. 39½° W. 23.6 ft.
marked 1/16 S. 24 P.S. 253 B.T.

Thence I run N. 86°59' W. on the south boundary of the N. W. ¼ of the N. E. ¼ of section 24.

At 1328.4 ft. I established the C. N. 1/16 S. 24. At this corner I set a 4" hemlock post marked CN 1/16 S. 24, from which;

A cedar 18" in diam. bears S. 76½° E. 44.0 ft.
marked C. N. 1/16 S. 24 P.S. 253 B. T.

A hemlock 15" in diam. bears N. 68° E. 29.1 ft.
marked C. N. 1/16 S. 24 P.S. 253 B.T.

Thence I run N. 88°10' W. on the south boundary of the N. E. ¼ of the N. W. ¼ of section 24.

At 1324.4 ft. I established the N. W. 1/16 S. 24. At this corner I set a 4" hemlock post marked N. W. 1/16 S. 24, from which;

FILED
RECEIVED

OCT 4 1955

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

42/20-c

A hemlock 16" in diam. bears S. 37° E. 32.6 ft.
marked N. W. 1/16 S. 24 P.S. 253 B.T.

A hemlock 16" in diam. bears S. 29½° W. 22.3 ft.
marked N. W. 1/16 S. 24 P.S. 253 B.T.

Thence I run S. 0°18' W. on the east boundary of the S. W. ¼ of
the N. W. ¼ of section 24.

At 1334.8 ft. I established the C. W. 1/16 S. 24. At this corner
I set a 3" hemlock post marked C. W. 1/16 S. 24, from which;

A fir 26" in diam. bears N. 24° E. 25.8 ft.
marked C. W. 1/16 S. 24 P.S. 253 B.T.

A fir 20" in diam. bears S. 62½° W. 21.2 ft.
marked C. W. 1/16 S. 24 P.S. 253 B.T.

Thence I run N. 87°16' W. on the E. & W. center line of section
24.

At 1329.0 ft. the original ¼ corner between section 23 & 24,
described above.

From the S. 1/16 S. 23 & 24, described above, I run S. 88°56' E.
on the north boundary of the S. W. ¼ of the S. W. ¼ of section 24.

At 1332.4 ft. I established the S. W. 1/16 S. 24. The exact
point for this corner falls within a 28" cedar tree, which I mark
S. W. 1/16 S. 24 P.S. 253, from which;

A hemlock 20" in diam. bears N. 76° E. 22.4 ft.
marked S. W. 1/16 S. 24 253 B.T.

A hemlock 12" in diam. bears S. 53° W. 35.5 ft.
marked S. W. 1/16 S. 24 253 B.T.

Thence I run S. 0°17' W. on the east boundary of the S. W. ¼ of
the S. W. ¼ of section 24.

At 1297.6 ft. the W. 1/16 S. 24 & 25, described above.

Survey completed September 9, 1955.

FILED
RECEIVED

OCT 4 1955

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

U. H. Hasford
[Signature Box]

At the corner common to sections 13, 14, 23, & 24, T. 25 S.,
R. 2 W., W. M., only one original bearing tree remains. I set a 3"
fir post marked S. 13, S. 14, S. 23, S. 24, 253, from which I mark
new B. T.'s as follows;

A fir 12" in diam. bears N. 32° E. 25.4 ft.
marked S. 13 253 B.T.

A fir 14" in diam. bears S. 8° E. 16.0 ft.
marked S. 24 253 B.T.

A fir 9" in diam. bears S. 54° W. 19.0 ft.
marked S. 23 253 B.T.

Original fir B. T., now 15" in diam.
bears N. 12° W. 21 links

October 13, 1955.

