

T 29 S R 3 W W.M. CDR. SECS.  $\frac{19}{30} \frac{20}{29}$

30" FIR N 70° E 62 lbs. set by HATHORNE IN 1857  
IS STILL STANDING AND PORTION OF BARK SCRIBING STILL  
VISIBLE. (TREE IS NOW 50") - RESCRIBE THIS TREE.

12" FIR S 74° E 30 lbs. GONE BUT DEPRESSION IN GROUND  
STILL SHOWS THAT A TREE ONCE STOOD THERE

12" MAPLE N 35° W 16 lbs. GONE BUT DEPRESSION IN  
GROUND AND MAPLE SPROUTS GROWING AROUND IT.

NO EVIDENCE OF 12" FIR S 52° W 37 lbs. - GROUND SHOWS  
EVIDENCE OF OLD SLIDE AREA.

SET IRON PIPE FOR CORNER AND MARK NEW TREES

- 28" CEDAR S 68° 15' E 42.2 FT.
- 28" CEDAR N 55° W 51.1 FT.
- 40" FIR S 27° 45' W 106.7 FT.

CORNER RENEWED IN APRIL, 1953 BY HALL - POTTER  
JOB. (JOB IN FILE)

SET BY E. S. WOODFORD  
WITNESS M. E. GODFREY  
CLIFF POTTER



FILED  
RECEIVED

JAN 19 1956

COUNTY SURVEYOR  
DOUGLAS COUNTY, ORE.

C.S. File No. 42/68-2

*JMD*