

SOUTH 1/4 COR. SEC 15  
T 24 S R 7 W W. M.

RESET: ... USING ERRONEOUS CORNER

15?  
22

(15/21) (SUPPOSEDLY DESTROYED)

SET IN 1893 FD. 54" FIR STUMP

S 43 W 18 LBS, WHIPPED OUT BT SCRIBES

FD 48" FIR STUMP N 51 E 31 LBS

WITH OLD FACES ROTTED OUT.

1/4 SEC 15 WAS RESET 2.65 CH  
EAST OF OLD COR., AT 2.54 CH EAST

I FOUND MAD STUMP BRS S 27 W, 25 LBS,  
(O. BT) AND STUMP HOLE OF FIR BEARS

N 07 W 20 LBS (O. BT), AT COR

POINT I SET A 3/8 X 30" WOOD BOLT

FROM WHICH A 40" FIR

BEARS N 40° 15' E, 58.7 FT

BLAZED & SCRIBED 45 15 RE 3561 BT

NO OTHER TREES AVAILABLE

WITNESS: TERRY MCDONALD

3 1/4 COR SEC 15

T 24 S 127 W 1 N. M.

DIETZEN NO. 385-B



**FILED  
RECEIVED**

**MAY 22 1956**

**COUNTY SURVEYOR  
DOUGLAS COUNTY, ORE.**